

> Inish Block

Block Paving



Pedestrian Traffic



Car & Light Vehicle Traffic

Technical Data Sheet

nssPlus

Q24 10
Q24 115
Q24 112
Q24 113


Features

- Concrete Block Paving
- Available with either a contemporary square edge or rustic tumbled edge to give the effect of a time worn cobble
- Can be laid in herringbone, stretcher bond and basket weave pattern depending on intended use
- Suitable for use on patios, paths, domestic driveways, commercial paths and for light traffic areas
- Available in 3 colours
- Standard Smooth surface finish or aged surface to give the effect of a time worn cobble

Product Range

	Dimensions (mm)	Colours	Pcs per m2	m2 per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile
Inish	200x50x60	Rustic, Curragh Gold, Charcoal	100	9	900	10	1060	Square edge
Inish Aged	200x50x60	Rustic, Curragh Gold, Charcoal	100	9	900	10	1060	Tumbled Square edge

Bold Text = in stock - Light Text = made to order (minimum order quantity applies)



Rustic



Curragh Gold



Charcoal



Rustic Aged



Curragh Gold Aged



Charcoal Aged

> Get In Touch:

T: +353 1 802 6300 technical@kilsaran.ie www.kilsaran.ie
T: +44 (0) 161 872 8899 www.kilsaraninternational.co.uk



Technical & Performance Data

Product Type	Concrete Block Paving	Application & Trafficking	Product suitable for both pedestrian and car traffic use when installed in conjunction with the correct, site specific sub-base design. Not recommended for truck/commercial vehicle traffic.
Product Standard	BS EN 1338:2003	Joint	Inish block paving has a narrow finish joint of 1mm approx. This product has no integral spacer nib and no chamfer and is suited to lower maintenance areas. Great care and attention must be paid when handling and installing to avoid chipping and damage to edges. Joints should be filled with Kiln dried sand.
Manufacturing Method	Hydraulically pressed semi-dry concrete	BREEAM	A rated in accordance with the Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base.
Finish	Mechanically distressed finish or squared edge option		
Packaging Information	Baled, strapped and plastic cover		
Slip/skid Resistance	Low potential - Typically USRV 60		
Strength	Typical tensile splitting strength of >3,6MPa and a failure load of >250N/mm		

Sustainability

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly products, manufacturing processes and continual product development.

All of our products are manufactured using industry leading best in class manufacturing facilities, reducing the impact our products have on the environment, as showcased with our newly awarded ISO 50001 certificate

Throughout our paving products we endeavour to replace 50% of the ordinary Portland cement with a high quality carbon neutral cement replacement Ground-granulated blast-furnace slag (GGBS), use 100% recycled water and locally sourced quality materials.

Making Kilsaran's extensive paving range, one of the most environmental friendly on the market.

Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

For further information, please contact Kilsaran's Technical Team: technical@kilsaran.ie

KILSARAN INTERNATIONAL
Piercetown
Dunboyne
Co. Meath
Ireland
A86 W820

T: 01 802 6300
E: info@kilsaran.ie
kilsaran.ie

KILSARAN INTERNATIONAL
Suite 30
1-3 The Courtyard
Calvin Street
Bolton
BL1 8PB

T: 0161 872 8899
E: info@kilsaraninternational.co.uk
kilsaraninternational.co.uk

