

> Slane Block

Technical Data Sheet

Traditional Block Paving



**nssPlus**

Q24 10  
Q24 115  
Q24 112  
Q24 113

**Features**

- Concrete Block Paving
- Can be laid in herringbone, stretcher bond and basketweave pattern depending on intended use
- Suitable for use on patios, paths, domestic driveways and commercial applications
- Various depth options available for different traffic loadings
- Available in 7 colours including our 100x100 cobble
- Standard Smooth finish
- Machine Lay version available
- Face-mix product to create an enhanced surface finish and better durability

**Product Range**

Dimensions (mm)	Colours	Pcs per m <sup>2</sup>	m <sup>2</sup> per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile
200x100x50	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	50	9.6	480	12	1060	Chamfer
200x100x60	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	50	9.6	480	12	1260	Chamfer
200x100x80	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	50	7.2	360	9	1195	Chamfer
300x300x80	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	11.1	6.48	72	9	1100	Square edge
300x200x80	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	16.6	6.72	112	7	1115	Square edge
200x200x80	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	50	6.72	168	7	1115	Square edge
100x100x60 (Cobble)	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	100	8	800	10	1020	Chamfer
100x100x80 (Cobble)	Rustic, Curragh Gold, Charcoal, Natural, Red, Buff, Brindle	100	6.72	672	7	1115	Square edge

**Bold Text = in stock** - Light Text = made to order (minimum order quantity applies)



Rustic



Curragh Gold



Charcoal



Natural



Red



Buff



Brindle

> Get In Touch:

T: +353 1 802 6300 [technical@kilsaran.ie](mailto:technical@kilsaran.ie) [www.kilsaran.ie](http://www.kilsaran.ie)  
T: +44 (0) 161 872 8899 [www.kilsaraninternational.co.uk](http://www.kilsaraninternational.co.uk)





## Technical & Performance Data

<b>Product Type</b>	Concrete Block Paving	<b>Application &amp; Trafficking</b>	Product suitable for both pedestrian, vehicular use and commercial goods traffic when correct block thickness is used in conjunction with the correct sub base design.
<b>Product Standard</b>	BS EN 1338:2003	<b>Joint</b>	Slane Paving has a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with Kiln dried jointing sand.
<b>Manufacturing Method</b>	Hydraulically pressed semi-dry concrete	<b>BREEAM</b>	'A' rated in accordance with the Green Guide Specification Edition 4, 2009 'A+' rated when used in conjunction with a prepared recycled sub-base.
<b>Finish</b>	Standard Smooth finish		
<b>Packaging Information</b>	Baled, strapped and plastic cover		
<b>Slip/skid Resistance</b>	Low potential - Typically USRV 60 FOR Standard Smooth, Typically USRV 65 for Textured		
<b>Strength</b>	Typical tensile splitting strength of >3,6MPa and a failure load of >250N/mm		

## Sustainability

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly products, manufacturing processes and continual product development.

**All of our products are manufactured using industry leading best in class manufacturing facilities, reducing the impact our products have on the environment, as showcased with our newly awarded ISO 50001 certificate**

Throughout our paving products we endeavour to replace 50% of the ordinary Portland cement with a high quality carbon neutral cement replacement Ground-granulated blast-furnace slag (GGBS), use 100% recycled water and locally sourced quality materials.

Making Kilsaran's extensive paving range, one of the most environmental friendly on the market.

## Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



### TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

**For further information, please contact Kilsaran's Technical Team: [technical@kilsaran.ie](mailto:technical@kilsaran.ie)**

**KILSARAN INTERNATIONAL**  
Piercetown  
Dunboyne  
Co. Meath  
Ireland  
A86 W820

**T: 01 802 6300**  
**E: [info@kilsaran.ie](mailto:info@kilsaran.ie)**  
[kilsaran.ie](http://kilsaran.ie)

**KILSARAN INTERNATIONAL**  
Suite 30  
1-3 The Courtyard  
Calvin Street  
Bolton  
BL1 8PB

**T: 0161 872 8899**  
**E: [info@kilsaraninternational.co.uk](mailto:info@kilsaraninternational.co.uk)**  
[kilsaraninternational.co.uk](http://kilsaraninternational.co.uk)

