

> Cashel Flag

Technical Data Sheet

Riven Finish Flag Paving



nssPlus

Q25 315

Q25 31

Features

- Concrete Flag Paving
- Riven Surface Finish
- Suitable for use on patios, paths and commercial pedestrian areas
- Can be laid in stack bond or stretcher bond depending on unit size(s)
- Available in 3 colours


Product Range

Dimensions (mm)	Colours	Pcs per m2	m2 per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile
400 x 400 x 40	Natural, Charcoal, Gold	6.25	13.44	84	14	1180	Chamfer

Bold Text = in stock - Light Text = made to order (minimum order quantity applies)



Natural



Charcoal



Gold



> Get In Touch:

T: +353 1 802 6300 technical@kilsaran.ie www.kilsaran.ie

T: +44 (0) 161 872 8899 www.kilsaraninternational.co.uk



Technical & Performance Data

Product Type	Concrete Flag	Application & Trafficking	Product suitable for pedestrian areas and commercial footpaths.
Product Standard	BS EN 1339:2003	Joint	Cashel Flags have a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joint should be filled with Kiln dried sand.
Manufacturing Method	Hydraulically pressed semi-dry concrete	BREEAM	A rated in accordance with the Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base
Finish	Riven standard finish		
Packaging Information	Baled, strapped and plastic cover		
Slip/skid Resistance	Low potential - Typically USRV 60		
Strength	Class 1 compliant to BS EN 1339:2003		

Sustainability

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly products, manufacturing processes and continual product development.

All of our products are manufactured using industry leading best in class manufacturing facilities, reducing the impact our products have on the environment, as showcased with our newly awarded ISO 50001 certificate

Throughout our paving products we endeavour to replace 50% of the ordinary Portland cement with a high quality carbon neutral cement replacement Ground-granulated blast-furnace slag (GGBS), use 100% recycled water and locally sourced quality materials.

Making Kilsaran's extensive paving range, one of the most environmental friendly on the market.

Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

For further information, please contact Kilsaran's Technical Team: technical@kilsaran.ie

KILSARAN INTERNATIONAL
Piercetown
Dunboyne
Co. Meath
Ireland
A86 W820

T: 01 802 6300
E: info@kilsaran.ie
kilsaran.ie

KILSARAN INTERNATIONAL
Suite 30
1-3 The Courtyard
Calvin Street
Bolton
BL1 8PB
T: 0161 872 8899
E: info@kilsaraninternational.co.uk
kilsaraninternational.co.uk

