

> Classic Flag

Technical Data Sheet

Traditional Flag Paving



Pedestrian
Traffic



Car & Light
Vehicle Traffic
*Class 3 only

nssPlus

Q25 315

Q25 31

Features

- Concrete Flag Paving
- Standard Smooth Surface Finish
- Suitable for use on patios, paths and commercial pedestrian areas
- Can be laid in stack bond or stretcher bond depending on unit size(s)
- Available in 5 colours

Product Range

Dimensions (mm)	Colours	Pcs per m ²	m ² per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile	Strength
400 x 400 x 40	Natural, Charcoal, Buff, Curragh, Rustic	6.25	13.44	80	20	1100	Chamfer	Class 1
450 x 450 x 40	Natural, Charcoal, Buff, Curragh, Rustic	4.94	12.96	64	16	1150	Square edge	Class 1
400 x 400 x 50	Natural, Charcoal	6.25	10.88	66	11	1170	Chamfer	Class 1
450 x 450 x 50	Natural, Charcoal, Buff, Curragh, Rustic	4.94	11.34	56	14	1232	Square edge	Class 1
600 x 600 x 50	Natural, Charcoal, Curragh Gold	2.77	10.8	30	15	1180	Chamfer	Class 1

Bold Text = in stock - Light Text = made to order (minimum order quantity applies)

Natural

Charcoal

Buff

Curragh Gold

Rustic

> Get In Touch:

T: +353 1 802 6300 technical@kilsaran.ie www.kilsaran.ie

T: +44 (0) 161 872 8899 www.kilsaraninternational.co.uk



Technical & Performance Data

Product Type	Concrete Flag
Product Standard	BS EN 1339:2003
Manufacturing Method	Hydraulically pressed semi-dry concrete
Finish	Standard Smooth finish
Packaging Information	Baled, strapped and plastic cover
Slip/skid Resistance	Low potential - Typically USRV 60
Strength	Compliant to BS EN 1339 2003

Application & Trafficking

Product suitable for pedestrian areas and commercial footpaths, light vehicular over-run can be accommodated using the correct thickness of flag (63mm or 80mm) when used in conjunction with the correct site specific sub-base design.

Joint

Classic Flags have a 1.5mm approx. Integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joint should be filled with Kiln dried sand.

BREEAM

A rated in accordance with the Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base.

Sustainability

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly products, manufacturing processes and continual product development.

All of our products are manufactured using industry leading best in class manufacturing facilities, reducing the impact our products have on the environment, as showcased with our newly awarded ISO 50001 certificate

Throughout our paving products we endeavour to replace 50% of the ordinary Portland cement with a high quality carbon neutral cement replacement Ground-granulated blast-furnace slag (GGBS), use 100% recycled water and locally sourced quality materials.

Making Kilsaran's extensive paving range, one of the most environmental friendly on the market.

Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

For further information, please contact Kilsaran's Technical Team: technical@kilsaran.ie

KILSARAN INTERNATIONAL

Piercetown
Dunboyne
Co. Meath
Ireland
A86 W820

T: 01 802 6300
E: info@kilsaran.ie
kilsaran.ie

KILSARAN INTERNATIONAL

Suite 30
1-3 The Courtyard
Calvin Street
Bolton
BL1 8PB

T: 0161 872 8899
E: info@kilsaraninternational.co.uk
kilsaraninternational.co.uk

