

> Textured Flag

Technical Data Sheet

Textured Concrete Flag Paving



Pedestrian  
Traffic



Car & Light  
Vehicle Traffic  
\*Class 3 only



Part of the  
Eco Paving Range

**nssPlus**

Q25 315

Q25 31

**Features**

- Concrete Flag Paving
- Lightly Textured Surface Finish
- Suitable for use on patios, paths and commercial pedestrian areas"
- Can be laid in stack bond or stretcher bond depending on unit size(s)
- Available in 3 colours

**Product Range**

Dimensions (mm)	Colours	Pcs per m2	m2 per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile	Strength
400 x 400 x 40	Natural, Charcoal, Buff	6.25	12.8	80	20	1180	Chamfer	Class 1
450 x 450 x 40	Natural, Charcoal, Buff	4.94	12.96	64	16	1150	Square edge	Class 1
400 x 400 x 50	Natural, Charcoal, Buff	6.25	11.52	72	12	1215	Chamfer	Class 1
450 x 450 x 50	Natural, Charcoal, Buff	4.94	11.34	56	14	1232	Square edge	Class 1
600 x 600 x 50	Natural, Charcoal, Buff	2.77	10.8	30	15	1180	Chamfer	Class 1

**Bold Text = in stock** - Light Text = made to order (minimum order quantity applies)

Natural

Charcoal

Buff

> Get In Touch:

T: +353 1 802 6300 [technical@kilsaran.ie](mailto:technical@kilsaran.ie) [www.kilsaran.ie](http://www.kilsaran.ie)

T: +44 (0) 161 872 8899 [www.kilsaraninternational.co.uk](http://www.kilsaraninternational.co.uk)





## Technical & Performance Data

<b>Product Type</b>	Concrete Flag	<b>Application &amp; Trafficking</b>	Product suitable for pedestrian areas and commercial footpaths, light vehicular over-run can be accommodated using the correct thickness of flag (63mm or 80mm) when used in conjunction with the correct site specific sub-base design.
<b>Product Standard</b>	BS EN 1339:2003	<b>Joint</b>	Textured Flags have a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joint should be filled with Kiln dried sand.
<b>Manufacturing Method</b>	Hydraulically pressed semi-dry concrete	<b>BREEAM</b>	A rated in accordance with the Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base.
<b>Finish</b>	Textured finish		
<b>Packaging Information</b>	Baled, strapped and plastic cover		
<b>Slip/skid Resistance</b>	Low potential - Typically USRV 60		
<b>Strength</b>	Compliant to BS EN 1339 2003		

## Sustainability

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly products, manufacturing processes and continual product development.

**All of our products are manufactured using industry leading best in class manufacturing facilities, reducing the impact our products have on the environment, as showcased with our newly awarded ISO 50001 certificate**

Throughout our paving products we endeavour to replace 50% of the ordinary Portland cement with a high quality carbon neutral cement replacement Ground-granulated blast-furnace slag (GGBS), use 100% recycled water and locally sourced quality materials.

Making Kilsaran's extensive paving range, one of the most environmental friendly on the market.

## Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



## TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

**For further information, please contact Kilsaran's Technical Team: [technical@kilsaran.ie](mailto:technical@kilsaran.ie)**

**KILSARAN INTERNATIONAL**  
Piercetown  
Dunboyne  
Co. Meath  
Ireland  
A86 W820

**T: 01 802 6300**  
**E: [info@kilsaran.ie](mailto:info@kilsaran.ie)**  
[kilsaran.ie](http://kilsaran.ie)

**KILSARAN INTERNATIONAL**  
Suite 30  
1-3 The Courtyard  
Calvin Street  
Bolton  
BL1 8PB

**T: 0161 872 8899**  
**E: [info@kilsaraninternational.co.uk](mailto:info@kilsaraninternational.co.uk)**  
[kilsaraninternational.co.uk](http://kilsaraninternational.co.uk)

