

> Quayside Flag

Technical Data Sheet

Unique Contemporary Concrete Flag Paving



Part of the
Eco Paving Range

NS5Plus

Q25 315

Q25 31

Features

- Concrete Flag Paving
- Suitable for use on patios, paths and commercial pedestrian areas
- Available in 3 standard colours, with the option to choose from our bespoke colour range as a special made to order. Terms and Conditions apply.

- Supplied as individual units 800x200/100x80mm as illustrated below
- Supplied in 80mm depth only
- Available in 3 types of finishes - Textured, Ground and Standard Smooth

Product Range

	Dimensions (mm)	Colours	Pcs per m ²	m ² per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile
Quayside (Textured)	800x200/100x80mmv	Silver Granite, Black Granite, Buff White	6.25	6.72	42	10	1200	Square edge
Quayside (Ground)	800x200/100x80mm	Silver Granite, Black Granite	6.25	6.72	42	10	1200	Square edge
Quayside (Standard Smooth)	800x200/100x80mm	Silver Granite, Black Granite, Buff White	6.25	6.72	42	10	1200	Square edge

Bold Text = in stock - Light Text = made to order (minimum order quantity applies)



BESPOKE
COLOUR OPTIONS
AVAILABLE



> Get In Touch:

T: +353 1 802 6300 technical@kilsaran.ie www.kilsaran.ie
T: +44 (0) 161 872 8899 www.kilsaraninternational.co.uk



Technical & Performance Data

Product Type	Concrete Flag
Product Standard	BS EN 1339:2003
Manufacturing Method	Hydraulically pressed semi-dry concrete
Finish	Textured, Ground and Standard Smooth
Packaging Information	Baled, strapped and plastic cover
Slip/skid Resistance	Medium to Low potential - Typically USRV 65 for textured, typically USRV 52 for ground, typically USRV 60 for Standard Smooth
Strength	Typically class 1 compliant to BS EN 1339:2003

Application & Trafficking

Product suitable for pedestrian areas and commercial footpaths, only when used in conjunction with the correct site specific sub-base design.

Joint

Quayside Flags has a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joint should be filled with Kiln dried sand or proprietary wide jointing compound approved for this product. Note that silver granite Kiln dried sand must be used for the silver colour option to reduce potential staining.

BREEAM

A rated in accordance with the Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base.

Eco Paving Range

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

All of our products are manufactured in our industry leading best in class manufacturing facilities to reduce the impact of our product range on our environment. All products are manufactured using 100% recycled water and using locally sourced quality materials.

Within our Eco Paving range we have developed and engineered a number of products with further reduced impact on the environment. The Eco Paving range is manufactured with a minimum of 25% non-primary aggregates, up to 10% pre consumer aggregate replacement and 50% of the ordinary Portland cement replaced with a carbon neutral high quality cement replacement.

Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

For further information, please contact Kilsaran's Technical Team: technical@kilsaran.ie

KILSARAN INTERNATIONAL

Piercetown
Dunboyne
Co. Meath
Ireland
A86 W820

T: 01 802 6300
E: info@kilsaran.ie
kilsaran.ie

KILSARAN INTERNATIONAL

Suite 30,
1-3 The Courtyard
Calvin Street
Bolton
BL1 8PB

T: 0161 872 8899
E: info@kilsaraninternational.co.uk
kilsaraninternational.co.uk

