

Declaration of Performance

DOP/GL/66674/47040

0/80 (75mm Down)

Gallstown, Grangebellew, Drogheda, Co Louth

1. Unique Identification code of the product - type: Code: 66674/47040 - 0/80 (75mm Down)

2. Intended use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction

3. Manufacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

6a. Harmonised Standard: I.S. EN 13242:2002+A1:2007

Notified Body: NSAI (0050-CPR-0495)

7. Declared Performance

| Characteristic | Declared Performance | | Harmonised Technical Specification |
|--|----------------------|-----------------------|------------------------------------|
| Particle size | Designation | 0/80 Ga75 | EN 933-1 |
| Particle shape | Category | NPD | EN 933-3 |
| Particle density | Declared Value | 2.8 Mg/m ³ | EN 1097-6 |
| Aggregate Type | Category | Greywacke | EN 932-3 |
| Fines content | Category | NPD | EN 933-1 |
| Percentage of crushed particles | Category | C _{100/0} | EN 933-5 |
| Resistance to fragmentation/crushing | Category | LA ₂₀ | EN 1097-2 |
| Water absorption/suction | Declared Value | WA ₂₄ 0.8 | EN 1097-6 |
| Acid soluble sulfate | Declared Value | AS _{NR} | EN 1744-1 |
| Total sulphur | Declared Value | S _{NR} | EN 1744-1 |
| Durability against freeze/thaw | Category | MS ₁₈ | EN 1367-2 |
| Resistance to wear | Category | NPD | EN 1097-1 |
| Fines quality | Category | NPD | EN 933-9 |
| Volume stability | Category | NPD | EN 1744-1 |
| Classification of coarse recycled aggregates | Category | NPD | EN 933-11 |
| Water soluble sulfates of recycled aggregates | Category | NPD | EN 1744-1 |
| Constituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD | EN 1744-1 |
| Release of heavy metals by leaching | Declared Value | NPD | EN 13242 |
| Release of other dangerous substances | Declared Value | NPD | EN 13242 |

8. N/A

<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thomas Little at Piercetown, Dunboyne, Co Meath on 26/05/2017





0050

Kilsaran Concrete
Piercetown, Dunboyne Co. Meath
16
0050-CPR-0495

I.S. EN 13242:2002+A1:2007
Aggregates for hydraulically bound and unbound material for civil engineering and road construction

0/80 (75mm Down)

Gallstown, Grangebellew, Drogheda, Co Louth

GL/66674/47040

| | | |
|--|----------------|-----------------------|
| Particle size | Designation | 0/80 Ga75 |
| Aggregate Type | | Greywacke |
| Particle shape | Category | NPD |
| Particle density | Declared Value | 2.8 Mg/M ³ |
| Cleanliness | | |
| Fines content | Category | NPD |
| Fines quality | Category | NPD |
| Percentage of crushed particles | Category | C _{100/0} |
| Resistance to fragmentation/crushing | Category | LA ₂₀ |
| Volume stability | Category | NPD |
| Water absorption/suction | Category | WA ₂₄ 2 |
| Composition/content | | |
| Classification of coarse recycled aggregates | Category | NPD |
| Water soluble sulfates of recycled aggregates | Category | NPD |
| Acid soluble sulfate | Category | AS _{NR} |
| Total sulphur | Category | S _{NR} |
| Constituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD |
| Resistance to wear | Category | NPD |
| Dangerous substances | | |
| Release of heavy metals by leaching | Declared Value | NPD |
| Release of other dangerous substances | Declared Value | NPD |
| Durability against freeze/thaw | Category | MS ₁₈ |