

Declaration of Performance

DOP/CT/68996

0/100 (100mm Down) Castletown Quarry, Rathmoylon, Co Meath

- 1. Unique Identification code of the product - type:** Code: 68996 - 0/100 (100mm Down)
- 2. Intended use/es:** Hydraulically bound and unbound materials for use in civil engineering and road construction
- 3. Manufacturer:** Kilsaran Concrete, Piercetown, Dunboyne Co. Meath
- 4. Authorised Representative:** N/A
- 5. System of AVCP:** System 2+
- 6a. Harmonised Standard:** I.S. EN 13242:2002+A1:2007 **Notified Body:** NSAI (0050-CPR-0210)
- 7. Declared Performance**

| Characteristic | Declared Performance | | Harmonised Technical Specification |
|--|----------------------|-----------------------|------------------------------------|
| Particle size | Designation | 0/100 Ga75 | EN 933-1 |
| Particle shape | Category | FI ₅₀ | EN 933-3 |
| Particle density | Declared Value | 2.7 Mg/m ³ | EN 1097-6 |
| Aggregate Type | Category | Limestone | EN 932-3 |
| Fines content | Category | NPD | EN 933-1 |
| Percentage of crushed particles | Category | C _{100/0} | EN 933-5 |
| Resistance to fragmentation/crushing | Category | LA ₃₀ | EN 1097-2 |
| Water absorption/suction | Declared Value | WA ₂₄ 0.4 | EN 1097-6 |
| Acid soluble sulfate | Declared Value | AS _{NR} | EN 1744-1 |
| Total sulphur | Declared Value | S _{NR} | EN 1744-1 |
| Durability against freeze/thaw | Category | MS ₁₈ | EN 1367-2 |
| Resistance to wear | Category | NPD | EN 1097-1 |
| Fines quality | Category | NPD | EN 933-9 |
| Volume stability | Category | NPD | EN 1744-1 |
| Classification of coarse recycled aggregates | Category | NPD | EN 933-11 |
| Water soluble sulfates of recycled aggregates | Category | NPD | EN 1744-1 |
| Constituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD | EN 1744-1 |
| Release of heavy metals by leaching | Declared Value | NPD | EN 13242 |
| Release of other dangerous substances | Declared Value | NPD | EN 13242 |

8. N/A

<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thomas Little at Piercetown, Dunboyne, Co Meath on 25/05/2017





0050

Kilsaran Concrete
Piercetown, Dunboyne Co. Meath
16
0050-CPR-0210

I.S. EN 13242:2002+A1:2007

**Aggregates for hydraulically bound and unbound material for
civil engineering and road construction**

0/100 (100mm Down)

Castletown Quarry, Rathmoylon, Co Meath
CT/68996

| | | |
|--|----------------|-----------------------|
| Particle size | Designation | 0/100 Ga75 |
| Aggregate Type | | Limestone |
| Particle shape | Category | FI ₅₀ |
| Particle density | Declared Value | 2.7 Mg/M ³ |
| Cleanliness | | |
| Fines content | Category | NPD |
| Fines quality | Category | NPD |
| Percentage of crushed particles | Category | C _{100/0} |
| Resistance to fragmentation/crushing | Category | LA ₃₀ |
| Volume stability | Category | NPD |
| Water absorption/suction | Category | WA ₂₄ 2 |
| Composition/content | | |
| Classification of coarse recycled aggregates | Category | NPD |
| Water soluble sulfates of recycled aggregates | Category | NPD |
| Acid soluble sulfate | Category | AS _{NR} |
| Total sulphur | Category | S _{NR} |
| Constituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD |
| Resistance to wear | Category | NPD |
| Dangerous substances | | |
| Release of heavy metals by leaching | Declared Value | NPD |
| Release of other dangerous substances | Declared Value | NPD |
| Durability against freeze/thaw | Category | MS ₁₈ |