

Declaration of Performance

DOP/BN/82673

4/40 (S.R. 21 ANNEX E - T2 PERM)

Ballinakill, Moate, Co Laois

1. Unique Identification code of the product - type:

Code 82673 - 4/40 (S.R. 21 ANNEX E - T2 PERM)

2. Intened use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction. Including unbound granular fill (Hardcore) for use under concrete floors and footpaths.

3. Manfacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

6a. Harmonised Standard: I.S. EN 13242:2002+A1:2007 / S.R. 21:2014+A1:2016 No

Notified Body: NSAI (0050-CPR-654)

7. Declared performance/s:

| Characteristic | Declared Performance | | Harmonised Technical Specification |
|---|----------------------|-----------------------|------------------------------------|
| Particle size | Designation | 4/40 | EN 933-1 |
| Particle shape | Category | NPD | EN 933-3 |
| Particle density | Declared Value | 2.6 Mg/m ³ | EN 1097-6 |
| Aggregate Type / Description | Limestone (PCG) | | EN 932-3 |
| Fines content | Category | NPD | EN 933-1 |
| Percentage of crushed particles | Category | C 100/0 | EN 933-5 |
| Resistance to fragmentation/crushing | Category | LA 30 | EN 1097-2 |
| Water absorption/suction | Declared Value | WA ₂₄ 1.7 | EN 1097-6 |
| Acid soluble sulfate | Declared Value | AS 0.04 | EN 1744-1 |
| Total sulphur | Declared Value | S 0.02 | EN 1744-1 |
| Durability against freeze/thaw | Category | MS 18 | EN 1367-2 |
| Resistance to wear | Category | NPD | EN 1097-1 |
| Fines quality | Category | NPD | EN 933-9 |
| Volume stability | Category | NPD | EN 1744-1 |
| Classification of coarse recycled aggregates | Category | NPD | EN 933-11 |
| Water soluble sulfates of recycled aggregates | Category | NPD | EN 1744-1 |
| Consitituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD | EN 1744-1 |
| Release of heavy metals by leaching | Declared Value | NPD | EN 13242 |
| Release of other dangerous substances | Declared Value | NPD | EN 13242 |

8. N/A

http://www.kilsaran.ie/build/technical-downloads/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thom tilles

Thomas Little at Piercetown, Dunboyne, Co Meath on 26/04/2018



CE

0050

Kilsaran Concrete Piercetown, Dunboyne Co. Meath

| 1 | 7 |
|---|---|
| | |

0050-CPR-654

I.S. EN 13242:2002+A1:2007 Aggregates for hydraulically bound and unbound material for civil engineering and road construction 4/40 (S.R. 21 ANNEX E - T2 PERM)

Ballinakill, Moate, Co Laois

BN/82673

| Particle size | Designation | 4/40 |
|---|-----------------|-----------------------|
| Aggregate Type / Description | Limestone (PCG) | |
| Particle shape | Category | NPD |
| Particle density | Declared Value | 2.6 Mg/M ³ |
| Cleanliness | | |
| Fines content | Category | NPD |
| Fines quality | Category | NPD |
| Percentage of crushed particles | Category | C 100/0 |
| Resistance to fragmentation/crushing | Category | LA 30 |
| Volume stability | Category | NPD |
| Water absorption/suction | Category | WA ₂₄ 2 |
| Composition/content | | |
| Classification of coarse recycled aggregates | Category | NPD |
| Water soluble sulfates of recycled aggregates | Category | NPD |
| Acid soluble sulfate | Category | AS 0.2 |
| Total sulphur | Category | S 1 |
| Consitituents which alter the rate of setting | | |
| and hardening of hydraulically bound mixtures | Category | NPD |
| Resistance to wear | Category | NPD |
| Dangerous substances | | |
| Release of heavy metals by leaching | Declared Value | NPD |
| Release of other dangerous substances | Declared Value | NPD |
| Durability against freeze/thaw | Category | MS 18 |