

Declaration of Performance

DOP/OV/93146

2/6.3mm (6mm)

Ovens Pit, Caseys Road, Ovens, Co Cork

1. Unique Identification code of the product - type:

Code: 93146 - 2/6.3 Gc85-20

2. Intended use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction

3. Manfacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 4

6a. Harmonised Standard: I.S. EN 13242:2002+A1:2007

7. Declared Performance

Characteristic	Declared Performance		Harmonised Technical Specification	
Particle size	Designation	2/6.3 Gc 85/20	EN 933-1	
Particle shape	Category	NPD	EN 933-3	
Particle density	Declared Value	2.6 Mg/m ³	EN 1097-6	
Aggregate Type	Category	Sandstone	EN 932-3	
Fines content	Category	f _{F1.5}	EN 933-1	
Resistance to fragmentation/crushing	Category	LA 25	EN 1097-2	
Water absorption/suction	Declared Value	WA ₂₄ 2.6	EN 1097-6	
Acid soluble sulfate	Declared Value	AS <0.1	EN 1744-1	
Total sulphur	Declared Value	S <0.1	EN 1744-1	
Durability against freeze/thaw	Category	MS ₈	EN 1367-2	
Resistance to wear	Category	M _{de} 30	EN 1097-1	
Fines quality	Category	NPD	EN 933-9	
Volume stability	Category	NPD	EN 1744-1	
Classification of coarse recycled aggregates	Category	NPD	EN 933-11	
Water soluble sulfates of recycled aggregates	Category	NPD	EN 1744-1	
Consitituents which alter the rate of setting and hardening of hydraulically bound mixtures	Category	NPD	EN 1744-1	
Release of heavy metals by leaching	Declared Value	NPD	EN 13242	
Release of other dangerous substances	Declared Value	NPD	EN 13242	

8. N/A

http://www.kilsaran.ie/build/technical-downloads/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stephen Greene at Piercetown, Dunboyne, Co Meath on 11.12.19

Stephen Greene



[

0050

Kilsaran Concrete Piercetown, Dunboyne Co. Meath

15

0

I.S. EN 13242:2002+A1:2007 Aggregates for hydraulically bound and unbound material for civil engineering and road construction

2/6.3mm (6mm)

Ovens Pit, Caseys Road, Ovens, Co Cork

OV/93146

Particle size	Designation	2/6.3 Gc 85/20	
Aggregate Type	Sandstone		
Particle shape	Category	NPD	
Particle density	Declared Value	2.6 Mg/M ³	
Cleanliness			
Fines content	Category	f _{F1.5}	
Fines quality	Category	NPD	
Resistance to fragmentation/crushing	Category	LA 25	
Volume stability	Category	NPD	
Water absorption/suction	Category	WA ₂₄ 2	
Composition/content			
Classification of coarse recycled aggregates	Category	NPD	
Water soluble sulfates of recycled aggregates	Category	NPD	
Acid soluble sulfate	Category	AS NR	
Total sulphur	Category	S _{NR}	
Consitituents which alter the rate of setting			
and hardening of hydraulically bound mixtures	Category	NPD	
Resistance to wear	Category	30	
Dangerous substances			
Release of heavy metals by leaching	Declared Value	NPD	
Release of other dangerous substances	Declared Value	NPD	
Durability against freeze/thaw	Category	MS ₈	