

Declaration of Performance

DOP/BM/51143

4/10 (10mm)

Ballynamona Pit, Summerhill, Co Meath

- 1. Unique Identification code of the product - type:** Code: 51143 - 4/10 (10mm)
- 2. Intened use/es:** Preparation of concrete for use in buildings, roads and other civil engineering works.
- 3. Manufacturer:** Kilsaran Concrete, Piercetown, Dunboyne Co. Meath
- 4. Authorised Representative:** N/A
- 5. System of AVCP:** System 2+
- 6a. Harmonised Standard:** I.S. EN 12620:2002+A1:2008 **Notified Body:** NSAI (0050-CPR-0594)
- 7. Declared Performance/s:**

Characteristic	Declared Performance		Harmonised Technical Specification
Particle Size	Designation	4/10 G _C 85/20	EN 933-1
Particle shape	Category	FI ₂₀	EN 933-3
Particle density	Declared Value	2.69 Mg/m ³	EN 1097-6
Aggregate Type / Description	Limestone (PCG)		EN 932-3
Fines content	Category	f _{1.5}	EN 933-1
Shell Content	Category	NPD	EN 933-7
Resistance to fragmentation/crushing	Category	LA ₃₀	EN 1097-2
Resistance to wear	Category	M _{de 20}	EN 1097-1
Resistance to Polishing	Category	NPD	EN 1097-8
Resistance to Abrasion	Category	NPD	EN 1097-8
Resistance to abrasion from studded tyres	Category	NPD	EN 1097-9
Constituents of coarse recycled aggregates	Category	NPD	EN 933-11
Chlorides	Declared Value	C (%) <0.001	EN 1744-1
Acid soluble sulfate	Declared Value	AS <0.1	EN 1744-1
Total sulphur	Declared Value	S <0.1	EN 1744-1
Water soluble sulfates of recycled aggregates	Category	NPD	EN 1744-1
Constituents which alter the rate of setting and hardening of concrete	Threshold Value	NPD	EN 1744-1
Influence of recycled aggregates on initial setting time of cement	Category	NPD	EN 1744-1
Carbonate Content	Declared Value	NPD	EN 196-2
Volume Stability - Drying Shrinkage	Threshold Value	Pass <0.075%	EN 1367-4
Constituents which affect the volume stability of air-cooled blastfurnace slag	Threshold Value	NPD	EN 1744-1
Water absorption	Declared Value	WA ₂₄ 1.5	EN 1097-6
Emmission of Radioactivity	Declared Value	NPD	EN 12620
Release of heavy metals	Threshold Value	NPD	EN 12620
Release of polyaromatic carbons	Threshold Value	NPD	EN 12620
Release of other dangerous substances	Declared Value	NPD	EN 12620
Durability against freeze/thaw	Category	MS ₁₈	EN 1367-2
Durability against alkali-silica reactivity	Declared Value	NPD	I.S. EN 12620:2002+A1:2008

8. N/A

<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stephen Greene at Piercetown, Dunboyne, Co Meath on 04/12/2024





0050

Kilsaran Concrete
Piercetown, Dunboyne Co. Meath
16
0050-CPR-0594

I.S. EN 12620:2002+A1:2008
Aggregates for Concrete

4/10 (10mm)

Ballynamona Pit, Summerhill, Co Meath
BM/51143

Particle size	Designation	4/10	G _c 85/20
Particle shape	Category		FI ₂₀
Particle density	Declared Value		2.69 Mg/m ³
Aggregate Type / Description			Limestone (PCG)
Cleanliness			
Fines content	Category		F _{1.5}
Shell Content	Category		NPD
Resistance to fragmentation/crushing	Category		LA ₃₀
Resistance to wear	Category		M _{de 20}
Resistance to Polishing	Category		NPD
Resistance to Abrasion	Category		NPD
Resistance to abrasion from studded tyres	Category		NPD
Composition/Content			
Constituents of coarse recycled aggregates	Category		NPD
Chlorides	Declared Value		C (%) <0.001
Acid soluble sulfate	Category		AS _{0.2}
Total sulphur	Category		S ₁
Water soluble sulfates of recycled aggregates	Category		NPD
Constituents which alter the rate of setting and hardening of concrete	Threshold Value		NPD
Influence of recycled aggregates on initial setting time of cement	Category		NPD
Carbonate Content	Declared Value		NPD
Volume Stability			
Drying Shrinkage	Threshold Value		Pass <0.075%
Constituents which affect the volume stability of air-cooled blastfurnace slag	Threshold Value		NPD
Water absorption	Declared Value		WA ₂₄ 1.5
Emmission of Radioactivity	Declared Value		NPD
Release of heavy metals	Threshold Value		NPD
Release of polyaromatic carbons	Threshold Value		NPD
Release of other dangerous substances	Declared Value		NPD
Durability against freeze/thaw	Category		MS ₁₈
Durability against alkali-silica reactivity	Declared Value		NPD

