


# **Declaration of Performance**

### DOP/KF/84591/84592

**15.0N 140mm Soap Bar** Kilfeacle, Co. Tipperary



1. Unique Identification code of the product - type: Code - 84591/84592 - 15.0N 140mm Soap Bar

2. Intended use: In Masonry walls, columns and partitions

3. Manufacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

6a. Harmonised Standard: I.S. EN 771-3:2011 Notified body: NSAI (0050 - CPR - 0583)

#### 7. Declared Performance

Characteristic	Declared Performance	Harmonised Technical Specification
Dimensions	(L x W x H) 440mm, 100mm, 140mm	I.S. EN 772-16
Dimensional Tolerances	Class D1	I.S. EN 772-16
Configuration	Category I, Group 1 unit	I.S EN 1996-1-1
Compressive Strength (Characteristic)	15.0N/mm²	I.S. EN 772-1
Dimensional Stability Moisture Movement	< 0.6mm/m	I.S. EN 772-14 / Table NA.7 EN 1996-1-1
ond Strength Shear Bond Strength	0.15N/mm²	I.S. EN 998-2 (Tabulated Value)
Flexural Bond Strength	NPD	N/A
Reaction to Fire	Class A1	I.S. EN 1996-1-2 Annex A (Tabulated Value)
Vater Absorption	NPD	N/A
Vater Vapour Permeability	5/15µ	I.S. EN 1745 Annex A (Tabulated Value)
Direct airborne sound insulation: Gross Dry Density	>1900kg/m³	I.S. EN 772-13
Configuration	As above	N/A
Dimensions and tolerances	As above	N/A
hermal Conductivity	0.90 - 1.00W/mK (λ10,dry Mat)	I.S. EN 1745 Annex A (Tabulated Value)
Durability Against Freeze Thaw	NPD (Not to be left exposed)	I.S. EN 771-3 - Ref: L Footnote
Dangerous Substances	NPD	See Note Below

8. N/A

## http://www.kilsaran.ie/build/technical-downloads/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Aboth

#### Chris O'Reilly at Piercetown, Dunboyne, Co.Meath on 03 August 2017

L: In the absence of a recognised and specific test method to determine the freeze-thaw resistance for aggreagte concrete masonry units, Table 14 of S.R. 325 should be consulted.



		I		
	(E			
		I		
	0050 Kilsaran Concre	te		
	Piercetown, Dunboyne (			
	17			
	0050 - CPR - 05	83		
	EN 771-3	_		
15.0N 140mm Soap Bar				
Category I - 440mm, 100mm, 140mm aggregate concrete masonry unit Kilfeacle, Co. Tipperary				
Dimensions	Declared value	(L x W x H) 440mm, 100mm, 140mm		
Dimensional Tolerences	Declared Category	Class D1		
Configurtion	Declared	Group 1 unit to I.S. EN 1996-1-1		
Compressive Strength	Characteristic	15.0N/mm²		
Dimensional Stability				
Moisture Movement	Declared Value	< 0.6mm/m		
Bond Strength				
Shear Bond Strength	Declared Value	0.15N/mm <sup>2</sup> (I.S. EN 998-2)(Tabulated Value)		
Flexural Bond Strength	Declared Value	NPD		
Reaction to Fire	Declared Class	A1 (I.S. EN 1996-1-2 Annex A)(Tabulated Value)		
Water Absorption	Declared Value	NPD		
Water Vapour Permeability	Declared Value	5/15µ (I.S. EN 1745 Annex A)(Tabulated Value)		
Direct airborne sound insulation:				
Gross Dry Density	Declared	>1900 kg/m <sup>3</sup>		
Configuration	Declared	100mm~ <sub>1∞</sub>		
		140mm		
Dimensions and tolerances	Declared	As above		
Thermal Conductivity	Declared Value 0.90 - 1.00 W/mK (λ10,dry Mat)(I.S. EN 1745 Annex A)(Tabulated Value)			
Durability Against Freeze Thaw	Declared - Ref: L Footnote	NPD (Not to be left exposed)		
Dangerous Substances	Declared	NPD		

L: In the absence of a recognised and specific test method to determine the freeze-thaw resistance for aggreagte concrete masonry units, Table 14 of S.R. 325 should be consulted.