

# Merrion Paving Flag



## BENEFITS

- Extremely robust due the increased cement content and Granite surface
- Cost reduction on supply and installation when compared to natural Granite and Porcelain
- Factory sealed application

## FEATURES

- Factory Pre-Sealed Concrete Flag Paving with Kilsaran K-Seal for full protection
- Lightly textured surface using premium granite aggregates
- The Merrion Flag features large visible contrasting stone chippings, offering a high-end finish similar to natural stone, granite, or terrazzo
- The paving flags come in a large 600x400 format, ideal for gardens and patio areas
- Can be laid in a variety of patterns depending on unit selected, please ask our technical team for laying pattern options
- Available in 3 unique finishes, including Pearl, Sapphire, and Quartz
- The 40mm Merrion clean edges and smooth texture mirror the latest design trends to achieve the desired contemporary look.

## COLOUR CHART



Pearl



Quartz



Sapphire

## PRODUCT RANGE

Dimensions mm	Colours	Pcs per m2	M2 per bale	Pcs per row	Pcs per Bale	Approx bale weight kg	Profile
600x400x40	Pearl, Sapphire, Quartz	4.2	11.52	24	48	788	Chamfer

Product Type	Concrete Flag Paving	Application & Trafficking	Product suitable for pedestrian traffic when designed and installed in conjunction with the correct, site specific sub-base design as per the relevant BS7533 standard.
Product Standard	EN 1339:2003		
Manufacturing Method	Hermetic SCC	Joint	Kilsaran recommend a joint width between 2mm-5mm as per BS 7533 to cater for jointing sand and product alignment (Butt jointing should be avoided) When jointing with Kiln dried sand, silver granite kiln dried sand must be used for the Pearl and Quartz colour option to reduce potential staining.
Spacer Nibs	No spacer nibs		
Finish	Textured granite aggregate finish		
Packaging Information	Baled, strapped on their side and plastic cover with ropes in between	BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base
Slip/Skid (Potential for Slip)	Extremely Low - USRV/PTV Above 75 for Shotblast finish, as per EN 1339:2003 Table NA.4		
Strength	Compliant to EN 1339:2003		

## TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products is available through our dedicated Technical & Sales team. Please contact Kilsaran's Technical Team: [technical@kilsaran.ie](mailto:technical@kilsaran.ie)

## ECO PAVING RANGE

Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

## Get in touch



ROI T: +353 (0)1 802 6300 E: [technical@kilsaran.ie](mailto:technical@kilsaran.ie) | [kilsaran.ie](http://kilsaran.ie)

UK T: +44 (0)161 872 8899 E: [info@kilsaraninternational.co.uk](mailto:info@kilsaraninternational.co.uk) | [kilsaraninternational.co.uk](http://kilsaraninternational.co.uk)