

## Declaration of Performance

DOP/225/48

**Trinity Paving Block**  
**Piercetown, Dunboyne, Co.Meath****1. Unique Identification code of the product** - type: Code - 225/48 - Trinity Paving Block**2. Intended use:** External Flooring**3. Manufacturer:** Kilsaran Concrete, Piercetown, Dunboyne, Co. Meath**5. System of AVCP:** System 4**6a. Harmonised Standard:** EN 1338:2003**7. Declared Performance**

Characteristic	Declared Performance	Harmonised Technical Specification
Reaction to Fire	Class A1	EN 1338 - 5.3.6.1
External Fire Performance	X	
Emissions of Asbestos	X	
Breaking Strength	≥ 3.6 MPa	EN 1338 - 5.3.3.2
Slip/Skid Resistance	> 45 (Low)	EN 1338 - 5.3.5.3
Thermal Conductivity	X	
Durability	Satisfactory	

**8.** N/A<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Chris O'Reilly at Piercetown, Dunboyne, Co.Meath on 18 January 2016****Position:** Quality Engineer



Kilsaran Concrete  
Piercetown, Dunboyne, Co. Meath  
18

**EN 1338**  
**Trinity Paving Block 80mm**

**Concrete paving block for use in (External Flooring)**

<b>Reaction to Fire:</b>	Class A1
<b>External Fire Performance</b>	X
<b>Emissions of Asbestos</b>	X
<b>Breaking Strength</b>	≥ 3.6 MPa
<b>Slip/Skid Resistance</b>	> 45 (Low)
<b>Thermal Conductivity:</b>	X
<b>Durability (against freeze-thaw):</b>	Satisfactory