

Massimo Paving Flag




BENEFITS

- Extremely robust due the increased cement content and Granite surface
- Cost reduction on supply and installation when compared to natural Granite and Porcelain

FEATURES

- Non textured & lightly textured surface using premium granite aggregates depending on the chosen colour
- 2mm integral spacer nibs which provide protection against chipped edges when laying and faster installation by achieving the correct joint width each time
- The paving flags come in a large 800x400 format, ideal for gardens and patio areas
- Can be laid in a variety of patterns depending on unit selected, please ask our technical team for laying pattern options
- Available in 5 unique finishes, including Pure, Blue, Sorrento, Silver Granite and Black Granite
- The 40mm Massimo has clean edges and smooth texture mirror the latest design trends to achieve the desired contemporary look.

COLOUR CHART



PRODUCT RANGE

Dimensions mm	Colours	Pcs per m2	M2 per bale	Pcs per Bale	Approx bale weight kg	Profile
800x400x40	Pure, Blue, Sorrento, Silver Granite, Black Granite	3.1	8.96	28	866	Chamfer

Product Type	Concrete Flag Paving	Application & Trafficking	Product suitable for pedestrian traffic when designed and installed in conjunction with the correct, site specific sub-base design as per the relevant BS7533 standard.
Product Standard	EN 1339:2003		
Manufacturing Method	Hermetic SCC	Joint	Kilsaran recommend a joint width between 2mm-5mm as per BS 7533 to cater for jointing sand and product alignment .When jointing with Kiln dried sand, silver granite kiln dried sand must be used for the Pure, Silver Granite and Sorrento colour option to reduce potential staining.
Spacer Nibs	2mm integral spacer nib		
Finish	Non textured and lightly textured granite aggregate finish		
Packaging Information	Baled, strapped on their side and plastic cover with ropes in between	BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base
Slip/Skid (Potential for Slip)	Extremely Low - USRV/PTV Above 75 for Shotblast finish, and Low potential– Typically USRV/PTV >60 for Non Textured finish as per EN 1339:2003 Table NA.4 and		
Strength	Compliant to EN 1339:2003		

TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products is available through our dedicated Technical & Sales team. Please contact Kilsaran's Technical Team: technical@kilsaran.ie

ECO PAVING RANGE

Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch

ROI T: +353 (0)1 802 6300 E: technical@kilsaran.ie | kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk | kilsaraninternational.co.uk