

Clima-Pave Grange Block Paving



BENEFITS

- Clima-Pave offers an advantage over traditional paving techniques as the system is constructed using our specially engineered permeable paving block
- Joints are enlarged on all sides, typically 4-8mm in width, which allows water to rapidly drain from the surface
- No need for gullies, channels or conventional drainage

FEATURES

- Concrete Block Paving
- Suitable for patios, pathways and domestic driveways
- Granite aggregate finish
- Available in 4 standard colours
- Supplied in 120mm depth only

COLOUR CHART



PRODUCT RANGE

Range	Dimensions mm	Colours	Pcs per m2	M2 per bale	Pcs per bale	No. Layers	Approx bale weight kg
Grange (Textured)	209x125x120mm	Silver Granite, Black Granite Autumn Brown, Autumn Oyster	N/A	N/A	N/A	N/A	N/A

Product Type	Concrete Block Paving	Application & Trafficking	Product suitable for pedestrian traffic & may be suitable for vehicular traffic when designed and installed in conjunction with the correct, site specific sub-base design as per the relevant BS7533 standard depending on the product size & depth.
Product Standard	EN 1338:2003		
Manufacturing Method	Hydraulically pressed semi dry concrete	Joint	Clima-Pave Grange Block Paving have a 4-8mm approx. internal spacers which will give a resulting standard joint width of approx. 2mm when laid. Jointing for a permeable system requires a 3mm washed grit. When jointing with kiln dried sand, silver granite kiln dried sand must be used for the silver and buff colour option to reduce potential staining.
Finish	Textured granite aggregate finish		
Packaging Information	Baled, strapped and plastic cover		
Slip/Skid Resistance	Extremely Low - USRV/PTV above 75, as per EN 1339:2003 Table NA.4.	Permeability	1800 litres/second/hectare
Strength	Compliant to EN 1338:2003		

TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products is available through our dedicated Technical & Sales team. Please contact Kilsaran's Technical Team: technical@kilsaran.ie

ECO PAVING RANGE

Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch



ROI T: +353 (0)1 802 6300 E: technical@kilsaran.ie | kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk | kilsaraninternational.co.uk