

KPRO LevelEase Primer Sealing Primer for Surfaces

Description

KPRO Floor LevelEase Primer is a high-performance, deep-penetrating primer designed to strengthen absorbent substrates and improve adhesion for subsequent layers. Suitable for both indoor and outdoor applications, it ensures reduced absorbency and enhanced workability for a wide range of surface preparation tasks. Its advanced formulation ensures reliable performance and durability, providing an optimal base for LevelEase 250, LevelEase 225 and LevelEase DUO 225.

Applications

KPRO Floor LevelEase Primer is ideal for priming walls, floors, and ceilings before:

- Fixing ceramic tiles.
- Pouring self-leveling floors.
- Applying floor linings, putties, or thermal insulation boards.
- Painting or papering.

Recommended for use on:

- Cement, cement-lime substrates, and screeds.
- Gypsum, anhydrite, and aerated concrete substrates.
- Chipboards and non-impregnated plasterboards.

Product Use

Ensure all surfaces are dry, load-bearing, and free from adhesion-reducing substances such as fats, bitumen, or dust. Remove weak layers, stains, and loose particles. Gypsum and anhydrite substrates should be sanded with coarse sandpaper, thoroughly cleaned, and vacuumed.

Application Instructions: Shake the product container well before use. Apply the primer evenly with a brush or roller. For very absorbent or loose substrates, dilute with clean water in a 1:1 ratio for the first coat. Apply additional coats undiluted if needed. For painting or flooring applications, ensure the primer dries completely before proceeding.

Packaging and Storage: Available in 5L bottle. Store in a cool, dry place, protected from frost.

Shelf life: 12 months in original, unopened packaging.

Technical Data

Application Temperature	Substrate and Ambient temperature must be between 5 °C and 25°C
Colour	Yellow
Base	Aqueous dispersion of synthetic resins
Density	~1.0 kg/dm ³
Drying Time	Approx.. 15 minutes (cement substrates) Approx 2 hours (other substrates)
Consumption	0.1 to 0.5 l/m ² (depending on substrate absorbency and evenness)

Disclaimer

All technical information provided is based on laboratory tests and practical experience. Results may vary depending on local conditions.

For further support or advice, contact **Kilsaran Technical**.



Benefits

- Suitable for all absorbent substrates.
- Strengthens and stabilizes the substrate surface.
- Reduces substrate absorbency to prevent rapid drying.
- Improves adhesion to substrates for optimal performance.
- Vapour permeable for breathability.
- Fast drying, enabling work to continue after only 15 minutes (on cement and cement-lime substrates).
- Facilitates the application of adhesives, fillers, putties, and flooring systems.

Application Temperatures



5°C to 30° C

Health & Safety

Please refer to the relevant Material Safety data sheet online at www.kilsaran.ie.

Pack Size

- 5 litre bottle

Get in touch:

ROI: T: 01 801 3484
UK: T: 0161 872 8899

Place an Order: orders@kilsaran.ie
Customer Service: csteam@kilsaran.ie

Tech Support: techsupport@kilsaran.ie
Website: www.kilsaran.ie