DECLARATION OF PERFORMANCE



In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014

DOP-CE No.

LevelEase Duo 225

1. Unique Identificatrion Code of the Product-Type: 112656

2. Intended Use:

Kilsaran Concrete declares, that the products named above, for use as a cementitious screed material for use internally in buildings, conforms to the provisions of Annex ZA of EN 13813, System 4

3. Manufacturer:

Kilsaran Concrete T/A Kilsaran, Piercetown Dunboyne Co. Meath Ireland, A86 W820

- 4. Authorised Representative: N/A
- 5. System(s) of AVCP:

System 4

6.a Harmonised Standard

EN 13813:2002

Noftified Body: N/A

7. Declared Perfomance(s)

Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire	NPD (not applicable for non-exposed floors)	EN 13501-1
Release of Corrosive Substances	СТ	EN 13813 (5.3.5)
Water Permeability	NPD	EN 1062-3
Water Vapour Permeability	NPD	EN 12086
Compressive Strength	C25	EN 13892-2
Flexural Strength	F6	EN 13892-2
Wear Resistance	NPD (not a wearing screed)	EN 13892 Part 3/4/5
Sound insulation	NPD	EN ISO 140-6
Sound Absorption	NPD	EN 12354-6
Thermal Resistance	NPD	EN 12524
Release of Dangerous Substance	See safety data sheet	EN 13813

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[Name] Ken Mulkerrins

At [Place] Piercetown

On [Date of Issue]

08/04/2025

[Signature]

	Kilsaran KPRO FACADES
	& MORTARS
(CE
	oncrete T/A Kilsaran
Piercetown, Dunboyne	e Co. Meath, Ireland A86 W820
	25 EN 13813
	Ease Duo 225
	e as a cementitious screed material for use internally in buildings, conforms t
the provisions of Ar	nnex ZA of EN 13813, System 4
Reaction to Fire	NPD (not applicable for non-exposed floors)
Release of Corrosive Substances	СТ
Water Permeability	NPD
Water Vapour Permeability	NPD
Compressive Strength	C25
Compressive Strength	C25
Flexural Strength	F6
Wear Resistance	NPD
Cound inculation	
Sound insulation	NPD
Sound Absorption	NPD
Thermal Resistance	NPD
Release of Dangerous Substances	See safety data sheet

DECLARATION OF PERFORMANCE



In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) as amended by the Construction Products (Amendment) (EU Exit) Regulations 2019 and the Construction Products (Amendment) (EU Exit) Regulations 2020

DOP-UKCA No.

LevelEase Duo 225

1. Unique Identificatrion Code of the Product-Type: 112656

2. Intended Use:

Kilsaran Concrete declares, that the products named above, for use as a cementitious screed material for use internally in buildings, conforms to the provisions of Annex ZA of EN 13813, System 4

3. Manufacturer:

Kilsaran Concrete T/A Kilsaran, Piercetown Dunboyne Co. Meath Ireland, A86 W820

- 4. Authorised Representative: N/A
- 5. System(s) of AVCP: System 4
- 6.a Harmonised Standard EN 13813:2002

Noftified Body: N/A

7. Declared Perfomance(s)

Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire	NPD (not applicable for non-exposed floors)	EN 13501-1
Release of Corrosive Substances	СТ	EN 13813 (5.3.5)
Water Permeability	NPD	EN 1062-3
Water Vapour Permeability	NPD	EN 12086
Compressive Strength	C25	EN 13892-2
Flexural Strength	F6	EN 13892-2
Wear Resistance	NPD (not a wearing screed)	EN 13892 Part 3/4/5
Sound insulation	NPD	EN ISO 140-6
Sound Absorption	NPD	EN 12354-6
Thermal Resistance	NPD	EN 12524
Release of Dangerous Substance	See safety data sheet	EN 13813

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance Regulation (EU) 305/2011 (Construction Product Regulation) as amended by the Construction Products (Amendment) (EU Exit) Regulations 2019 and the Construction Products (Amendment) (EU Exit) Regulations 2020, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[Name]

Ken Mulkerrins

At [Place] Piercetown

On [Date of Issue]

08/01/2025

[Signature]

	Kilsaran KPRO FACADES & MORTARS		
	UK CA		
Kilsaran (Concrete T/A Kilsaran		
	ne Co. Meath, Ireland A86 W820		
25			
EN 13813			
	elEase Duo 225		
	use as a cementitious screed material for use internally in buildings, conforms to Annex ZA of EN 13813, System 4		
Reaction to Fire	NPD (not applicable for non-exposed floors)		
Release of Corrosive Substances	СТ		
Water Permeability	NPD		
Water Vapour Permeability	NPD		
Compressive Strength	C25		
Flexural Strength	F6		
Wear Resistance	NPD (not a wearing screed)		
Sound insulation	NPD		
Sound Absorption	NPD		
Thermal Resistance	NPD		
Release of Dangerous Substances	See safety data sheet		