

Declaration of Performance

DOP/BR/111472

4/12.5 (12.5mm)

Brownstown, Kilcullen, Co Kildare

- 1. Unique Identification code of the product - type:** Code: 111472 - 4/12.5 (12.5mm)
- 2. Intended use/es:** Preparation of concrete for use in buildings, roads and other civil engineering works.
- 3. Manufacturer:** Kilsaran Concrete, Piercetown, Dunboyne Co. Meath
- 4. Authorised Representative:** N/A
- 5. System of AVCP:** System 2+
- 6a. Harmonised Standard:** I.S. EN 12620:2002+A1:2008 **Notified Body:** CTI-CEM -2845
- 7. Declared Performance/s:**

Characteristic	Declared Performance	Harmonised Technical Specification
Particle Size	Designation 4/12.5 G _C 85/20	EN 933-1
Particle shape	Category FI ₁₅	EN 933-3
Particle density	Declared Value 2.65 Mg/m ³	EN 1097-6
Aggregate Type / Description	Limestone (PCG)	EN 932-3
Fines content	Category f _{1.5}	EN 933-1
Shell Content	Category NPD	EN 933-7
Resistance to fragmentation/crushing	Category LA ₂₅	EN 1097-2
Resistance to wear	Category M _{de 15}	EN 1097-1
Resistance to Polishing	Category NPD	EN 1097-8
Resistance to Abrasion	Category NPD	EN 1097-8
Resistance to abrasion from studded tyres	Category NPD	EN 1097-9
Constituents of coarse recycled aggregates	Category NPD	EN 933-11
Chlorides	Declared Value C (%) <0.015	EN 1744-1
Acid soluble sulfate	Declared Value AS <0.1	EN 1744-1
Total sulphur	Declared Value S <0.1	EN 1744-1
Water soluble sulfates of recycled aggregates	Category NPD	EN 1744-1
Constituents which alter the rate of setting and hardening of concrete	Threshold Value NPD	EN 1744-1
Influence of recycled aggregates on initial setting time of cement	Category NPD	EN 1744-1
Carbonate Content	Declared Value NPD	EN 196-2
Volume Stability - Drying Shrinkage	Threshold Value Pass <0.075%	EN 1367-4
Constituents which affect the volume stability of air-cooled blastfurnace slag	Threshold Value NPD	EN 1744-1
Water absorption	Declared Value WA ₂₄ 1	EN 1097-6
Emmission of Radioactivity	Declared Value NPD	EN 12620
Release of heavy metals	Threshold Value NPD	EN 12620
Release of polyaromatic carbons	Threshold Value NPD	EN 12620
Release of other dangerous substances	Declared Value NPD	EN 12620
Durability against freeze/thaw	Category MS ₁₈	EN 1367-2
Durability against alkali-silica reactivity	Declared Value NPD	I.S. EN 12620:2002+A1:2008

8. N/A

<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stephen Greene at Piercetown, Dunboyne, Co Meath on 25th September 2025





2845

Kilsaran Concrete
Piercetown, Dunboyne Co. Meath
24
2845

I.S. EN 12620:2002+A1:2008
Aggregates for Concrete

4/12.5 (12.5mm)

Brownstown, Kilcullen, Co Kildare
BR/111472

Particle size	Designation	4/12.5	G _C 85/20
Particle shape	Category	FI	15
Particle density	Declared Value	2.65	Mg/m ³
Aggregate Type / Description		Limestone (PCG)	
Cleanliness			
Fines content	Category	F	1.5
Shell Content	Category	NPD	
Resistance to fragmentation/crushing	Category	LA	25
Resistance to wear	Category	M _{de}	15
Resistance to Polishing	Category	NPD	
Resistance to Abrasion	Category	NPD	
Resistance to abrasion from studded tyres	Category	NPD	
Composition/Content			
Constituents of coarse recycled aggregates	Category	NPD	
Chlorides	Declared Value	C (%)	<0.015
Acid soluble sulfate	Category	AS	0.2
Total sulphur	Category	S	1
Water soluble sulfates of recycled aggregates	Category	NPD	
Constituents which alter the rate of setting and hardening of concrete	Threshold Value	NPD	
Influence of recycled aggregates on initial setting time of cement	Category	NPD	
Carbonate Content	Declared Value	NPD	
Volume Stability			
Drying Shrinkage	Threshold Value	Pass	<0.075%
Constituents which affect the volume stability of air-cooled blastfurnace slag	Threshold Value	NPD	
Water absorption	Declared Value	WA ₂₄	1
Emmission of Radioactivity	Declared Value	NPD	
Release of heavy metals	Threshold Value	NPD	
Release of polyaromatic carbons	Threshold Value	NPD	
Release of other dangerous substances	Declared Value	NPD	
Durability against freeze/thaw	Category	MS	18
Durability against alkali-silica reactivity	Declared Value	NPD	