

Patio Bedding Mix

Description

Kilsaran KPRO Crete Patio Bedding Mix is a bedding mix specifically formulated for the bedding and installation of paving units for patios and other domestic outdoor paved areas.

Applications

Kilsaran KPRO Crete Patio Bedding Mix can be used for the following applications,

- Bedding of patio flags
- Bedding of patio steps
- Bedding of patio circles and step stones

Product Use

Preparation: Suitable for use in temperatures between +5°C and +30°C. The subgrade should be clean dry and not liable to subsidence. Poor subgrades can be improved using a layer of compacted Cl. 804.

Mixing: Kilsaran Patio Bedding Mix should be mixed with 2.2-2.6 litres of clean potable water to create a semi-dry bedding mix.

Placing: Spread out a layer of the freshly mixed material on the area to be paved and screed off to leave a consistent bedding layer approximately 50mm-55mm in depth. Lift the paving flags into place and tamp into position with a pavers maul, ensuring the paving flag is fully embedded into the fresh Patio Bedding Mix. Allow at least 24 hours before opening to foot traffic.

Technical Data

KPRO Crete Patio Bedding Mix is produced in an ISO 9001 quality-controlled environment.

Characteristic	Data value
Colour	Standard Grey
Density	1900 kg/m ³
Polypropylene Fibres	Available upon request



Benefits

- Consistently high-quality mix
- Eliminates inaccurate site mixing
- Suitable for construction of all foot trafficked patio areas.
- Convenient and User-Friendly
- Eliminates wastage
- Promotes cleaner and safer sites

Approximate Yield

No. 25kg Bags	Approximate m ³
1	0.01
2	0.02
5	0.06
10	0.1
20	0.2
40	0.5

Application Temperatures



+5°C to +30°C

Health & Safety

Please refer to the relevant Material Safety data sheet online at www.kilsaran.ie.

Pack Size

- 25kg premixed bags

Get in touch



ROI T: +353 (0)1 802 6300 E: technicaladmin@kilsaran.ie kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk kilsaraninternational.co.uk