

Belvedere Flags

Features

- Riven surface finish
- Irregular edge profile
- 50 & 60mm Depth
- Suitable for use on patios, paths and commercial pedestrian areas

Product Range

i roudot rtaligo								
Range	Dimensions (mm)	Colours	Pcs Per m2	m2 Per bale	Pcs Per bale	No. Layers	Approx. Bale Weight (KG)	Profile
Belvedere Standard Flags	(4 size-mix) 200 x 200 x 60/50 400 x 200 x 60/50 400 x 400 x 60/50 600 x 400 x 60/50	Curragh Gold, Charcoal	N/A	11.5	84	12	1200	Irregular Edge
Belvedere Flags (Curled)	(4 size-mix) 200 x 200 x 60/50 400 x 200 x 60/50 400 x 400 x 60/50 600 x 400 x 60/50	Silver Granite	N/A	11.5	84	12	1200	Irregular Edge

Mixed pack of 4 sizes

• Laid in a random bond pattern

Bold Text = in stock - Light Text = made to order (minimum order quantity applies)

200	600	400		
X	x	X		
200mm	400mm	400mm		
200 x 200mm	400mm	400mm		
400	200	600		
x	x	x		
400mm	400mm	400mm		

Unit sizes and quantities, as supplied.

Application & Trafficking	Product suitable for pedestrian areas and commercial footpaths, light car only over-run can be accommodated in conjunction with the correct site specific sub-base design. Not suitable for driveway use.
Joint	Belvedere Paving has a 4-6mm approx. integral spacer rib which will give a resulting standard joint width of approx. 6-8mm when laid. Joints should be filled with Kiln dried jointing sand or a proprietary wide jointing compound approved for this product.
BREEAM	"A' rated in accordance with the Green Guide Specification Edition 4, 2009 'A+' rated when used in conjunction with a prepared recycled sub-case

Technical Support

Product Type

Finish

Strength

Product Standard

Manufacturing Method

Packaging Information

Slip/Skid Resistance

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

Compliant to EN 1339:2003

For further information, please contact Kilsaran's **Technical Team:** technical@kilsaran.ie

Concrete Flag

Riven

Low potential

BS EN 1339:2003

Hydraulically pressed semi dry concrete

Baled, strapped and plastic cover

Eco Paving Range Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch

ROI T: +353 (0)1 802 6300 E: technicaladmin@kilsaran.ie kilsaran.ie UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk kilsaraninternational.co.uk





Charcoal



Curragh Gold



