



Excellence is our Passion

DECLARATION OF PERFORMANCE

No. 00264

1. Unique identification code of the product-type:

CERESIT CT 74

External and internal plaster on organic binders

2. Type, batch or serial number or any other element allowing identification of the construction product:

The badge number is printed on the packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification:

Silicone plaster with "pebbles" texture is designed for applying thin-coat plasters on the concrete, traditional plasters, gypsum substrates as well as chipboards, and gypsum cardboards

4. Name registered trade name or registered trade mark and contact address of the manufacturer:

It is marketed by:

Henkel Polska Sp. z o.o.

ul. Domaniewska 41

02-672 Warszawa

It is produced in:

Production plant in Stąporków

26-220 Stąporków

Stara Góra

5. If appropriate, the name and contact address of the authorized representative:

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product:

System 4

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

EN 15824:2009 Requirements for external and internal plasters based on organic binders

Centralne Laboratorium Badawcze

Henkel Polska Sp. z o.o.

Stara Góra

26-220 Stąporków

conducted:

The determination of conformity with the standard PN-EN 15824:2009 technical parameters of the product CT 74

8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9. Declared performance:


| Essential characteristics | Performance | Harm. techn. Spec. |
|---|------------------------------|--------------------|
| Reaction to fire | Class F | EN 13501-1 |
| Adhesion | 0,6 N/mm ² | EN 15824 |
| Water absorption | W ₂ | EN 15824 |
| Water vapour permeability μ | V ₂ | EN 15824 |
| Thermal conductivity $\lambda_{10,div}$ | 0,61 W/m*K (tabulated value) | EN 15824 |
| Durability | NPD | EN 15824 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mariusz Garecki
Chief Specialist of Quality
and Implementation

GLÓWNY SPECJALISTA
ds. Jakości i Wdrożeń

dr inż. Mariusz Garecki

Stąporków, 01.07.2013
(place and date of issue)

Piotr Urynek
Manager of Quality Control Department


(name and function)