



Excellence is our Passion

**DECLARATION OF PERFORMANCE
No. 00268**

1. Unique identification code of the product-type:

CERESIT CT 79

External and internal plaster on organic binders

2. Type, batch or serial number or any other element allowing identification of the construction product:

The badge number is printed on the packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification:

Ready to use elastomeric plaster recommended to use on the exterior division walls where high mechanical resistance is required

4. Name registered trade name or registered trade mark and contact address of the manufacturer:

It is marketed by:

**Henkel Polska Sp. z o.o.
ul. Domaniewska 41
02-672 Warszawa**

It is produced in:

**Production plant in Stąporków
26-220 Stąporków
Stara Góra**

5. If appropriate, the name and contact address of the authorized representative:

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product:

System 4

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

EN 15824:2009 Requirements for external and internal plasters based on organic binders

**Centralne Laboratorium Badawcze
Henkel Polska Sp. z o.o.
Stara Góra
26-220 Stąporków**

conducted:

**The determination of conformity with the standard PN-EN 15824:2009
technical parameters of the product CT 79**

8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A


9. Declared performance:

| Essential characteristics | Performance | Harm. techn. Spec. |
|-----------------------------------------|------------------------------|--------------------|
| Reaction to fire | Class F | EN 13501-1 |
| Adhesion | 0,6 N/mm ² | EN 15824 |
| Water absorption | W ₂ | EN 15824 |
| Water vapour permeability μ | V ₂ | EN 15824 |
| Thermal conductivity $\lambda_{10,div}$ | 0,61 W/m*K (tabulated value) | EN 15824 |
| Durability | NPD | EN 15824 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mariusz Garecki
Chief Specialist of Quality
and Implementation
GŁÓWNY SPECJALISTA
(name and function)
ds. Jakości i Wdrożeń

dr inż. Mariusz Garecki

Piotr Urynek
Manager of Quality Control Department
(name and function)


Stąporków, 01.07.2013
(place and date of issue)