



Excellence is our Passion

## DECLARATION OF PERFORMANCE

No. 00269

1. Unique identification code of the product-type:

**CERESIT CT 174**

**External and internal plaster on organic binders**

2. Type, batch or serial number or any other element allowing identification of the construction product:

**The badge number is printed on the packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification:

**Silicate-silicone plaster with "pebbles" texture is designed for applying thin-coat plasters on the concrete, traditional plasters, gypsum substrates as well as chipboards, and gypsum cardboards**

4. Name registered trade name or registered trade mark and contact address of the manufacturer:

It is marketed by:

**Henkel Polska Sp. z o.o.**

**ul. Domaniewska 41**

**02-672 Warszawa**

It is produced in:

**Production plant in Stąporków**

**26-220 Stąporków**

**Stara Góra**

5. If appropriate, the name and contact address of the authorized representative:

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product:

**System 4**

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

**EN 15824:2009 Requirements for external and internal plasters based on organic binders**

**Centralne Laboratorium Badawcze**

**Henkel Polska Sp. z o.o.**

**Stara Góra**

**26-220 Stąporków**

conducted:

**The determination of conformity with the standard PN-EN 15824:2009 technical parameters of the product CT 174**

8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**N/A**

9. Declared performance:

Essential characteristics	Performance	Harm. techn. Spec.
Reaction to fire	Class F	EN 13501-1
Adhesion	0,6 N/mm <sup>2</sup>	EN 15824
Water absorption	W <sub>2</sub>	EN 15824
Water vapour permeability $\mu$	V <sub>2</sub>	EN 15824
Thermal conductivity $\lambda_{10,div}$	0,61 W/m*K (tabulated value)	EN 15824
Durability	NPD	EN 15824

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Mariusz Garecki  
Chief Specialist of Quality  
and Implementation  
**GŁÓWNY SPECJALISTA**  
(name and function)  
ds. Jakości i Wdrożeń  
  
dr inż. Mariusz Garecki

Stąporków, 01.07.2013  
(place and date of issue)

Piotr Urynek  
Manager of Quality Control Department  
  
(name and function)