

Declaration of Performance

DOP/225/03-1

Blister Tactile Paving Flag Piercetown, Dunboyne, Co.Meath

 $\textbf{1. Unique Identification code of the product} \ \text{- type: Code - } \ 225/03\text{-}1 \ \text{- Blister Tactile Paving Flag}$

2. Intended use: External Flooring

3. Manufacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

5. System of AVCP: System 4**6a. Harmonised Standard:** EN 1339

7. Declared Performance

Characteristic	Declared Performance	Harmonised Technical Specification
Reaction to Fire	Class A1	EN 1339 - 5.3.7.1
External Fire Performance	Х	
Emissions of Asbestos	X	
Breaking Strength	≥ 3.5 MPa	EN 1339 - 5.3.3
Slip/Skid Resistance	> 45 (Low)	EN 1339 - 5.3.5
Thermal Conductivity	X	
Durability	Satisfactory	

8. N/A

http://www.kilsaran.ie/build/technical-downloads/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Chris O'Reilly at Piercetown, Dunboyne, Co.Meath on 18th January 2016

Position: Quality Engineer





Kilsaran Concrete Piercetown, Dunboyne Co. Meath 14

EN 1339 Blister Tactile Paving Flag 50mm

Concrete paving block for use in (External Flooring) Reaction to Fire: Class A1 External Fire Performance **Emissions of Asbestos** Breaking Strength ≥ 3.5 MPa Slip/Skid Resistance > 45 (Low) Thermal Conductivity: Satisfactory Durability (against freeze-thaw):