

Declaration of Performance

DOP/225/08

Mellifont Paving Block
Piercetown, Dunboyne, Co.Meath

1. Unique Identification code of the product - type: Code - 225/08 - Mellifont Paving Block

2. Intended use: External Flooring

3. Manufacturer: Kilsaran Concrete, Piercetown, Dunboyne, Co. Meath

5. System of AVCP: System 4

6a. Harmonised Standard: EN 1338:2003

7. Declared Performance

| Characteristic | | Declared Performance | Harmonised Technical Specification |
|---------------------------|--|----------------------|------------------------------------|
| Reaction to Fire | | Class A1 | EN 1338 - 5.3.6.1 |
| External Fire Performance | | Х | |
| Emissions of Asbestos | | Х | |
| Breaking Strength | | ≥ 3.6 MPa | EN 1338 - 5.3.3.2 |
| Slip/Skid Resistance | | > 45 (Low) | EN 1338 - 5.3.5.3 |
| Thermal Conductivity | | X | |
| Durability | | Satisfactory | |

8. N/A

http://www.kilsaran.ie/build/technical-downloads/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Chris O'Reilly at Piercetown, Dunboyne, Co.Meath on 26 November 2015

Position: Quality Engineer

At Men





Kilsaran Concrete Piercetown, Dunboyne, Co. Meath 14

EN 1338 Mellifont Paving Block 50mm, 60mm, 80mm

Concrete paving block for use in (External Flooring) Reaction to Fire: Class A1 **External Fire Performance Emissions of Asbestos** Breaking Strength ≥ 3.6 MPa Slip/Skid Resistance > 45 (Low) Thermal Conductivity: Satisfactory Durability (against freeze-thaw):