

Declaration of Performance

DOP/225/14

Clima-Pave Lismore Paving Block
Piercetown, Dunboyne, Co.Meath

1. Unique Identification code of the product - type: Code - 225/14 - Clima-Pave Lismore Paving Block

2. Intended use: External Flooring

3. Manufacturer: Kilsaran Concrete, Piercetown, Dunboyne, Co. Meath

5. System of AVCP: System 4

6a. Harmonised Standard: EN 1338:2003

7. Declared Performance

Characteristic	Declared Performance	Harmonised Technical Specification
Reaction to Fire	Class A1	EN 1338 - 5.3.6.1
External Fire Performance	X	
Emissions of Asbestos	X	
Breaking Strength	≥ 3.6 MPa	EN 1338 - 5.3.3.2
Slip/Skid Resistance	> 45 (Low)	EN 1338 - 5.3.5.3
Thermal Conductivity	X	
Durability	Satisfactory	

8. N/A

<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Chris O'Reilly at Piercetown, Dunboyne, Co.Meath on 18 January 2016

Position: Quality Engineer





Kilsaran Concrete
Piercetown, Dunboyne, Co. Meath
14

EN 1338
Clima-Pave Lismore Paving Block 60mm, 80mm
Concrete paving block for use in (External Flooring)

Reaction to Fire:	Class A1
External Fire Performance	X
Emissions of Asbestos	X
Breaking Strength	≥ 3.6 MPa
Slip/Skid Resistance	> 45 (Low)
Thermal Conductivity:	X
Durability (against freeze-thaw):	Satisfactory