

Inish Block Paving

Features

- Concrete Block Paving
- Available with either a contemporary edge (Inish) or rustic tumbled edge to give the effect of a time worn cobble (Inish Aged)
- Can be laid in a herringbone, stretcher bond or basket weave pattern depending on the intended use
- Available in 3 standard colours
- Suitable for use on patios, paths, domestic driveways, commercial paths and for light traffic areas

Product Range

Dimensions (mm)	Colours	Pcs Per m2	m2 Per bale	Pcs Per bale	No. Layers	Approx. Bale Weight (KG)	Profile
Inish	Rustic, Curragh Gold, Charcoal	100	9	900	10	1060	Square Edge
Inish Aged	Rustic, Curragh Gold, Charcoal	28	11	308	11	1250	Antiqued

Bold Text = in stock – **Light Text** = made to order (minimum order quantity applies)



Colour Chart



Product Type	Concrete Block Paving
Product Standard	EN 1338:2003
Manufacturing Method	Hydraulically pressed semi dry concrete
Finish	Mechanically distressed finish or squared edge option
Packaging Information	Baled, strapped and plastic cover
Slip/Skid Resistance	low – Typically USRV/PTV >60
Strength	Typical tensile splitting strength of >3.6 MPa and a failure load of >250N/mm

Application & Trafficking	Installation to BS 7533-2:2001. Please refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com Product suitable for both pedestrian and commercial use
Joint	Corrib Block Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand. Note that silver granite kiln dried sand must be used for the silver and buff colour option to reduce potential staining.
BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base

Technical Support

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

For further information, please contact Kilsaran's **Technical Team:** technical@kilsaran.ie

Eco Paving Range Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch



ROI T: +353 (0)1 802 6300 E: technicaladmin@kilsaran.ie kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk kilsaraninternational.co.uk