

Heavy Textured Concrete Block Paving



Pedestrian Traffic



Car & Light Vehicle Traffic



Heavy Duty Traffic



Part of the Eco Paving Range

**nssPlus**

- Q24 10
- Q24 115
- Q24 112
- Q24 113

**Features**

- Concrete Block Paving
- Heavy textured surface finish using premium granite aggregates
- Various depth options available for different traffic loadings
- Can be laid in a variety of patterns depending on unit selected, please ask our technical team for laying pattern options
- Available in 6 colours
- Supplied in a three size mix (240x160/160x160/120x160 single size 240x160x80 also available)

**Product Range**

Dimensions (mm)	Colours	Pcs per m2	m2 per bale	Pcs per Bale	No. Layers	Approx. Bale Weight (KG)	Profile
3 size 60	Silver Granite, Black Granite, Rustic, Curragh Gold, Charcoal, Natural	35	9.6	350	10	1190	Square edge
3 size 80	Silver Granite, Black Granite, Rustic, Curragh Gold, Charcoal, Natural	35	6.72	245	7	1190	Square edge
240x160x80	Silver Granite, Black Granite, Rustic, Curragh Gold, Charcoal, Natural	27	6.72	175	7	1075	Square edge

**Bold Text = in stock** - Light Text = made to order (minimum order quantity applies)



> Get In Touch:

T: +353 1 802 6300 [technical@kilsaran.ie](mailto:technical@kilsaran.ie) [www.kilsaran.ie](http://www.kilsaran.ie)  
T: +44 (0) 161 872 8899 [www.kilsaraninternational.co.uk](http://www.kilsaraninternational.co.uk)



## Technical & Performance Data

<b>Product Type</b>	Concrete Block Paving
<b>Product Standard</b>	BS EN 1338:2003
<b>Manufacturing Method</b>	Hydraulically pressed semi-dry concrete
<b>Finish</b>	Pin Hammered heavy textured finish
<b>Packaging Information</b>	Baled, strapped and plastic cover
<b>Slip/skid Resistance</b>	Low potential - Typically USRV 70
<b>Strength</b>	Typical tensile splitting strength of >3,6MPa and a failure load of >250N/mm

<b>Application &amp; Trafficking</b>	Product suitable for both pedestrian, vehicular use and commercial traffic when installed in conjunction with the correct, site specific sub-base design.
<b>Joint</b>	Tara Block Paving have a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joint should be filled with Kiln dried sand. Note that silver granite Kiln dried sand must be used for the silver colour option to reduce potential staining.
<b>BREEAM</b>	A rated in accordance with the Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base.

## Eco Paving Range

Kilsaran is committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

**All of our products are manufactured in our industry leading best in class manufacturing facilities to reduce the impact of our product range on our environment. All products are manufactured using 100% recycled water and using locally sourced quality materials.**

Within our Eco Paving range we have developed and engineered a number of products with further reduced impact on the environment. The Eco Paving range is manufactured with a minimum of 25% non-primary aggregates, up to 10% pre consumer aggregate replacement and 50% of the ordinary Portland cement replaced with a carbon neutral high quality cement replacement.

## Maintenance and Cleaning

Kilsaran recommends regularly cleaning on an annual basis is performed, for more information please contact our technical team or download our Maintenance and Cleaning document from our website.



## TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

**For further information, please contact Kilsaran's Technical Team: [technical@kilsaran.ie](mailto:technical@kilsaran.ie)**

**KILSARAN INTERNATIONAL**  
Piercetown  
Dunboyne  
Co. Meath  
Ireland  
A86 W820

**T: 01 802 6300**  
**E: [info@kilsaran.ie](mailto:info@kilsaran.ie)**  
[kilsaran.ie](http://kilsaran.ie)

**KILSARAN INTERNATIONAL**  
Suite 30  
1-3 The Courtyard  
Calvin Street  
Bolton  
BL1 8PB

**T: 0161 872 8899**  
**E: [info@kilsaraninternational.co.uk](mailto:info@kilsaraninternational.co.uk)**  
[kilsaraninternational.co.uk](http://kilsaraninternational.co.uk)



[Kilsaran.home](http://Kilsaran.home)



[@kilsaran](https://twitter.com/@kilsaran)

