

Cashel Flag Paving



BENEFITS

- The Cashel flag offers a rugged natural stone look that is both strong and durable.
- Perfect for patios, the riven surface effect replicates the rustic appeal of natural stone.
- Extremely robust due the increased cement content

COLOUR CHART



Natural



Charcoal



Gold

FEATURES

- Concrete Flag Paving
- Riven surface finish
- Can be laid in stack bond or stretcher bond depending on unit size(s)
- Available in 3 standard colours
- Suitable for use on patios, paths and commercial pedestrian areas

PRODUCT RANGE

| Dimensions mm | Colours | Pcs per m2 | M2 per bale | Pcs per bale | Pcs per Layers | Approx bale weight kg | Profile |
|---------------|-------------------------|------------|-------------|--------------|----------------|-----------------------|---------|
| 400x400x40 | Natural, Charcoal, Gold | 6.25 | 13.44 | 84 | 6 | 1180 | Chamfer |

| | | | |
|--------------------------------|---|---------------------------|--|
| Product Type | Concrete Flag Paving | Application & Trafficking | Product suitable for pedestrian traffic when designed and installed in conjunction with the correct, site specific sub-base design as per the relevant BS7533 standard. |
| Product Standard | EN 1339:2003 | | |
| Manufacturing Method | Hydraulically pressed semi dry concrete | Joint | Cashel Flag Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand when installed in an unbound construction. |
| Finish | Riven surface finish | | |
| Packaging Information | Baled, strapped and plastic cover | | |
| Slip/Skid (Potential for Slip) | Low - USRV/PTV 40-74, as per EN 1339:2003 Table NA.4. Test values typically >60 | BREEAM | A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base |
| Strength | Compliant to EN 1339:2003 | | |

TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products is available through our dedicated Technical & Sales team. Please contact Kilsaran's Technical Team: technical@kilsaran.ie

ECO PAVING RANGE

Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch



ROI T: +353 (0)1 802 6300 E: technical@kilsaran.ie | kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk | kilsaraninternational.co.uk