

Classic Flag Paving



BENEFITS

- Extremely robust due to the increased cement content in the surface
- The Classic Flag Paving keeps the declared slip resistance of extremely low throughout its life cycle
- Cost reduction on supply and installation when compared to natural Granite and Porcelain


COLOUR CHART



Buff




Charcoal



Curragh Gold



Natural



Rustic

FEATURES

- Concrete Flag Paving
- Standard smooth finish
- Suitable for use on patios, paths and commercial pedestrian areas
- Can be laid in stack bond or stretcher bond depending on unit size(s)
- Available in 5 standard colours
- Bespoke colours available upon request

PRODUCT RANGE

Dimensions mm	Colours	Pcs per m2	M2 per bale	Pcs per bale	No. Layers	Approx bale weight kg	Profile
400x400x40	Natural, Charcoal, Buff, Curragh Gold, Rustic	6.25	13.44	84	14	1155	Chamfer
450x450x40	Natural, Charcoal, Buff, Curragh Gold, Rustic	4.94	12.96	64	16	1150	Square Edge
400x400x50	Natural, Charcoal, Buff, Curragh Gold, Rustic	6.25	11.52	72	12	1240	Chamfer
450x450x50	Natural, Charcoal, Buff, Curragh Gold, Rustic	4.94	11.34	56	14	1232	Square Edge
600x600x50	Natural, Charcoal, Buff, Curragh Gold, Rustic	2.77	10.8	30	15	1180	Chamfer

Product Type	Concrete Flag Paving	Application & Trafficking	Product suitable for pedestrian traffic & may be suitable for vehicular traffic when designed and installed in conjunction with the correct, site specific sub-base design as per the relevant BS7533 standard depending on the product size & depth.
Product Standard	EN 1339:2003		
Manufacturing Method	Hydraulically pressed semi dry concrete	Joint	Classic Flag Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand for an unbound surface. Note that silver granite kiln dried sand must be used for the silver colour option to reduce potential staining.
Finish	Standard smooth finish		
Packaging Information	Baled, strapped and plastic cover	BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base
Slip/Skid (Potential for Slip)	Low - USRV/PTV 40-74, as per EN 1339:2003 Table NA.4. Test values typically >60		
Strength	Compliant to EN 1339:2003		

TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products is available through our dedicated Technical & Sales team. Please contact Kilsaran's Technical Team: technical@kilsaran.ie

ECO PAVING RANGE

Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch



ROI T: +353 (0)1 802 6300 E: technical@kilsaran.ie | kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk | kilsaraninternational.co.uk