

Declaration of Performance

DOP/GL/8022-8132

SMA 14 Surf 70/100 des PSV60

Gallstown, Grangebellew, Drogheda, Co Louth

- 1. Unique Identification code of the product - type:** Code 8022-8132 / SMA 14 Surf 70/100 des PSV60
- 2. Intened use/es:** For surface courses, binder courses, regulating courses and bases of roads, and other trafficked areas, whether subject or not to reaction to fire regulations.
- 3. Manufacturer:** Kilsaran Concrete, Piercetown, Dunboyne Co. Meath
- 4. Authorised Representative:** N/A
- 5. System of AVCP:** System 2+
- 6a. Harmonised Standard:** I.S. EN 13108-5:2006 & S.R. 28 **Notified Body:** NSAI (0050-CPR-042)
- 7. Declared Performance/s**

Characteristic	Declared Performance		Harmonised Technical Specification
Binder content:	Declared Value	B _{act} 5.7	EN 12697-39
	Category	B _{min} 5.8	
Binder Drainage:	Category	NPD	EN 12697-18
Grading (% passing)	1.4D	Values 20mm 100	EN 12697-2
	D	14mm 95	
	Characteristic coarse	10mm 52	
	2	2mm 23	
	0,063	0.063mm 8.0	
Temperature of the mixture	Threshold Value	140°C to 180°C	EN 12697-13
Void content:			EN 12697-13
-Maximum / Minimum	Category	NPD	EN 12697-8
Void filled with Bitumen:			
-Maximum / Minimum	Category	NPD	
Void in mineral aggregate	Category	NPD	
Water sensitivity	Category	NPD	EN 12697-12
Resistance to abrasion by studded tyres	Category	NPD	EN 12697-16
Reaction to fire	Euroclass	NPD	EN 13501-1
Resistance to permanent deformation	Category	NPD	EN 12697-22
Stiffness	Category	NPD	EN 12697-26
Resistance to fuel	Category	NPD	EN 12697-43
Resistance to de-icing fluid	Category	NPD	EN 12697-40
Dangerous substances	Declared Value	NPD	EN 13108-5 Annex ZA.3

8. N/A

<http://www.kilsaran.ie/build/technical-downloads/>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thomas Little at Piercetown, Dunboyne, Co Meath on 23 November 2015





0050

Kilsaran Concrete
Piercetown, Dunboyne Co. Meath
15

0050-CPR-042

I.S. EN 13108-5

Asphalt Concrete for roads and trafficked areas

SMA 14 Surf 70/100 des PSV60

Gallstown, Grangebellew, Drogheda, Co Louth

GL/8022-8132

Void content:

-Maximum / Minimum	Category	NPD
--------------------	----------	-----

Voids filled with bitumen

-Maximum / Minimum	Category	NPD
--------------------	----------	-----

Voids in mineral aggregate

Water sensitivity	Category	NPD
--------------------------	----------	-----

Resistance to abrasion by studded tyres	Category	NPD
--	----------	-----

Reaction to fire	Euroclasses	NPD
-------------------------	-------------	-----

Resistance to fuel	Category	NPD
---------------------------	----------	-----

Resistance to de-icing fluid	Category	NPD
-------------------------------------	----------	-----

Temperature of the mixture	Threshold Value	140°C to 180°C
-----------------------------------	-----------------	----------------

Grading (% passing)	Declared Values	20mm	100
		14mm	95
		10mm	52
		2mm	23
		0.063mm	8.0

Binder content:	Declared Value	B _{act} 5.7
	Category	B _{min} 5.8

Binder Drainage:	Category	NPD
-------------------------	----------	-----

Resistance to permanent deformation	Category	NPD
--	----------	-----

Stiffness

-Minimum	Category	NPD
----------	----------	-----

-Maximum	Category	NPD
----------	----------	-----

Resistance to fatigue	Category	NPD
------------------------------	----------	-----

Dangerous substances	Declared Value	NPD
-----------------------------	----------------	-----