

Killeen Flag Paving



BENEFITS

- Extremely robust due to the increased cement content and Granite surface
- Unlike Natural Granite and Porcelain, the Killeen Flag Paving keeps the declared slip resistance of extremely low throughout its life cycle
- Cost reduction on supply and installation when compared to natural Granite and Porcelain

FEATURES

- Concrete Flag Paving
- Suitable for use on patios, paths, domestic driveways and commercial pedestrian areas
- Available in a 70mm depth, supplied as a mix of 4 sizes as shown
- Can be laid in a random bond pattern Silver Granite
- Available in 3 standard colours
- Available in 3 types of finishes - Shotblasted, Ground and Standard
- Available in permeable option

PRODUCT RANGE

Range	Dimensions mm	Colours	Pcs per m2	M2 per bale	Pcs per bale	No. Layers	Approx bale weight kg	Profile
Killeen (Standard)	4 Co-Ordinating Mixed Sizes as shown	Silver Granite, Black Granite, Slate	N/A	7.56	72	9	1180	Irregular Edge
Killeen (Shotblasted)		Silver Granite, Black Granite, Slate	N/A	7.56	72	9	1180	Irregular Edge
Killeen (Ground)		Silver Granite, Black Granite, Slate	N/A	7.56	72	9	1180	Irregular Edge

COLOUR CHART



Product Type	Concrete Flag Paving	Application & Trafficking	Product suitable for both pedestrian & vehicular traffic when designed and installed in conjunction with the correct, site specific sub-base design as per the relevant BS7533 standard.
Product Standard	EN 1339:2003		
Manufacturing Method	Hydraulically pressed semi dry concrete	Joint	Killeen Flag Paving have a 4-6mm approx. internal spacer nib which will give a resulting standard joint width of approx. 6-8mm when laid. Joints should be filled with kiln dried sand for an unbound construction. Note that silver granite kiln dried sand must be used for the silver colour option to reduce potential staining.
Finish	Shotblasted, Standard Smooth and Ground finish		
Packaging Information	Baled, strapped and plastic cover	BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub-base
Slip/Skid (Potential for Slip)	Low - USRV/PTV 40-74, for Standard and Ground finishes, Extremely Low - USRV/PTV Above 75 for Shotblast finish, as per EN 1339:2003 Table NA.4.		
Strength	Compliant to EN 1339:2003		

TECHNICAL SUPPORT

Help with the preparation of specifications using any of Kilsaran's hard landscaping products is available through our dedicated Technical & Sales team. Please contact Kilsaran's Technical Team: technical@kilsaran.ie

ECO PAVING RANGE

Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch



ROI T: +353 (0)1 802 6300 E: technical@kilsaran.ie | kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk | kilsaraninternational.co.uk