

Textured Flag Paving

Features

- Concrete Flag Paving
- Lightly Textured Surface Finish
- Suitable for use on patios, paths and commercial pedestrian areas
- Can be laid in stack bond or stretcher bond depending on unit size(s)
- Available in 3 colours

Product Range

| Dimensions (mm) | Colours | Pcs Per m2 | m2 Per bale | Pcs Per bale | No. Layers | Approx. Bale Weight (KG) | Profile | Strength |
|-----------------|-------------------------|------------|-------------|--------------|------------|--------------------------|-------------|----------|
| 400x400x40 | Natural, Charcoal, Buff | 6.25 | 12.80 | 80 | 20 | 1180 | Chamfer | Class 1 |
| 450x450x40 | Natural, Charcoal, Buff | 4.94 | 12.96 | 64 | 16 | 1150 | Square Edge | Class 1 |
| 400x400x50 | Natural, Charcoal, Buff | 6.25 | 11.52 | 72 | 12 | 1215 | Chamfer | Class 1 |
| 450x450x50 | Natural, Charcoal, Buff | 4.94 | 11.34 | 56 | 14 | 1232 | Square Edge | Class 1 |
| 600x600x40 | Natural, Charcoal, Buff | 2.77 | 10.8 | 30 | 15 | 1180 | Chamfer | Class 1 |

Bold Text = in stock – **Light Text** = made to order (minimum order quantity applies)



| | |
|------------------------------|---|
| Product Type | Concrete Flag |
| Product Standard | BS EN 1339:2003 |
| Manufacturing Method | Hydraulically pressed semi dry concrete |
| Finish | Textured Finish |
| Packaging Information | Baled, strapped and plastic cover |
| Slip/Skid Resistance | Low potential – Typically USRV 60 |
| Strength | Compliant to BS EN 1339:2003 |

| | |
|--------------------------------------|--|
| Application & Trafficking | Installation to BS 7533-4:2006. Please refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com Product suitable for pedestrian use only |
| Joint | Textured Flags have a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joint should be filled with Kiln dried sand. |
| BREEAM | "A" rated in accordance with the Green Guide Specification Edition 4, 2009 'A+' rated when used in conjunction with a prepared recycled sub-case |

Technical Support

Help with the preparation of specifications using any of Kilsaran's hard landscaping products, including design, BIM and NBS is available through our dedicated technical team and regional sales office.

For further information, please contact Kilsaran's **Technical Team:**
technical@kilsaran.ie

Eco Paving Range Kilsaran are committed to leading the way in the industry with sustainable and environmentally friendly product manufacturing and continual product development.

Get in touch



ROI T: +353 (0)1 802 6300 E: technicaladmin@kilsaran.ie kilsaran.ie

UK T: +44 (0)161 872 8899 E: info@kilsaraninternational.co.uk kilsaraninternational.co.uk