



Joint Tec Jointing Compound fixing mortar – the solution to your pavement joint problems! Dimensions of Joints; Joint Width: Min. 5mm Joint Depth: Min. 20mm Fuge is a one-component, ready to use jointing mortar, suitable for natural stone, concrete and slate pavers. It is permanently water permeable, prevents weeds from sprouting. Fuge is easy to apply, and thanks to the unique "all weather formula" it can be applied regardless of weather conditions.

Steps to application:

Step 1: Prep the area, cleaning the slabs so they are free from debris and ensuring the joints are a minimum of 20mm deep and 5mm wide.

Step 2: Wet the area, ensuring slabs are fully saturated prior to spreading Joint Tec

Step 3: Apply the product by pouring product out of the vac packed bag onto areas to be pointed. Use in small manageable amounts.

Step 4: Work the grout into the joints using a stiff brush or squeegee brush whilst continuously washing the compound into the joints with a hose/sprinkler.

Step 5: Wash and clean the surface with a gentle spray of water to wash off any residue. Always sweep and brush diagonally to the joints.

Colours:

Sand and Stone Grey

Pack Size:

15Kg Bucket.

Coverage:

Approx. 6m² per bucket



Get in Touch

IRELAND - T: +353 (0)1 802 6300 - **E:** technical@kilsaran.ie - **W:** www.kilsaran.ie

UK - T: +44 (0)161 872 8899 - **E:** technical@kilsaraninternational.co.uk - **W:** www.kilsaraninternational.co.uk