

Declaration of Performance

DOP/BA/78769

4/40 (S.R. 21 ANNEX E - T2 PERM)

Ballinascorney, Brittas, Co Dublin

1. Unique Identification code of the product - type:

Code 78769 - 4/40 (S.R. 21 ANNEX E - T2 PERM)

2. Intened use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction. Including unbound granular fill (Hardcore) for use under concrete floors and footpaths.

3. Manfacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

6a. Harmonised Standard: I.S. EN 13242:2002+A1:2007 / S.R. 21:2014+A1:2016

Notified Body: NSAI (0050-CPR-0499)

7. Declared performance/s:

Characteristic	Declared Performance		Harmonised Technical Specification
Particle size	Designation	4/40	EN 933-1
Particle shape	Category	NPD	EN 933-3
Particle density	Declared Value	2.8 Mg/m ³	EN 1097-6
Aggregate Type / Description	Dolerite/Greywacke		EN 932-3
Fines content	Category	NPD	EN 933-1
Percentage of crushed particles	Category	C 100/0	EN 933-5
Resistance to fragmentation/crushing	Category	LA 20	EN 1097-2
Water absorption/suction	Declared Value	WA ₂₄ 0.8	EN 1097-6
Acid soluble sulfate	Declared Value	AS <0.1	EN 1744-1
Total sulphur	Declared Value	S <0.1	EN 1744-1
Durability against freeze/thaw	Category	MS 18	EN 1367-2
Resistance to wear	Category	NPD	EN 1097-1
Fines quality	Category	NPD	EN 933-9
Volume stability	Category	NPD	EN 1744-1
Classification of coarse recycled aggregates	Category	NPD	EN 933-11
Water soluble sulfates of recycled aggregates	Category	NPD	EN 1744-1
Consitituents which alter the rate of setting and hardening of hydraulically bound mixtures	Category	NPD	EN 1744-1
Release of heavy metals by leaching	Declared Value	NPD	EN 13242
Release of other dangerous substances	Declared Value	NPD	EN 13242

8. N/A

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thom tilles

Thomas Little at Piercetown, Dunboyne, Co Meath on 28/05/2019



CE

0050

Kilsaran Concrete Piercetown, Dunboyne Co. Meath 16

0050-CPR-0499

I.S. EN 13242:2002+A1:2007 Aggregates for hydraulically bound and unbound material for civil engineering and road construction

4/40 (S.R. 21 ANNEX E - T2 PERM)

Ballinascorney, Brittas, Co Dublin

BA/78769

Particle size	Designation	4/40	
Aggregate Type / Description	Dolerit	Dolerite/Greywacke	
Particle shape	Category	NPD	
Particle density	Declared Value	2.8 Mg/M ³	
Cleanliness			
Fines content	Category	NPD	
Fines quality	Category	NPD	
Percentage of crushed particles	Category	C 100/0	
Resistance to fragmentation/crushing	Category	LA 20	
Volume stability	Category	NPD	
Water absorption/suction	Category	WA ₂₄ 2	
Composition/content			
Classification of coarse recycled aggregates	Category	NPD	
Water soluble sulfates of recycled aggregates	Category	NPD	
Acid soluble sulfate	Category	AS 0.2	
Total sulphur	Category	S 1	
Consitituents which alter the rate of setting			
and hardening of hydraulically bound mixtures	Category	NPD	
Resistance to wear	Category	NPD	
Dangerous substances			
Release of heavy metals by leaching	Declared Value	NPD	
Release of other dangerous substances	Declared Value	NPD	
Durability against freeze/thaw	Category	MS 18	