

Declaration of Performance

DOP/CT/78771

0/125 (S.R. 21 ANNEX E - TO STRUC)

Castletown Quarry, Rathmoylon, Co Meath

1. Unique Identification code of the product - type:

Code 78771 - 0/125 (S.R. 21 ANNEX E - T0 STRUC)

2. Intened use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction. Including unbound granular fill (Hardcore) for use under concrete floors and footpaths.

3. Manfacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

6a. Harmonised Standard: I.S. EN 13242:2002+A1:2007 / S.R. 21:2014+A1:2016 Notified Body: CTI-CEM (2845) **7. Declared performance/s:**

| Characteristic | Characteristic Declared Performance | | Harmonised Technical Specification |
|---|-------------------------------------|-----------------------|------------------------------------|
| Particle size | Designation | 0/125 | EN 933-1 |
| Particle shape | Category | NPD | EN 933-3 |
| Particle density | Declared Value | 2.7 Mg/m ³ | EN 1097-6 |
| Aggregate Type / Description | Limestone | | EN 932-3 |
| Fines content | Category | f 9 | EN 933-1 |
| Percentage of crushed particles | Category | C 100/0 | EN 933-5 |
| Resistance to fragmentation/crushing | Category | LA 30 | EN 1097-2 |
| Water absorption/suction | Declared Value | WA ₂₄ 0.6 | EN 1097-6 |
| Acid soluble sulfate | Declared Value | AS 0.1 | EN 1744-1 |
| Total sulphur | Declared Value | S _{0.1} | EN 1744-1 |
| Durability against freeze/thaw | Category | MS 18 | EN 1367-2 |
| Resistance to wear | Category | NPD | EN 1097-1 |
| Fines quality | Category | NPD | EN 933-9 |
| Volume stability | Category | NPD | EN 1744-1 |
| Classification of coarse recycled aggregates | Category | NPD | EN 933-11 |
| Water soluble sulfates of recycled aggregates | Category | NPD | EN 1744-1 |
| Consitituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD EN 1744-1 | |
| Release of heavy metals by leaching | Declared Value | NPD | EN 13242 |
| Release of other dangerous substances | Declared Value | NPD | EN 13242 |

8. N/A

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stephen Greene

Stephen Greene at Piercetown, Dunboyne, Co Meath on 20th February 2025



| INTER | | | | |
|--|------------------|-----------------------|--|--|
| | | | | |
| | 6 | | | |
| | | | | |
| _ | | | | |
| O Kilsaran C | `oncrete | | | |
| Piercetown, Dunb | | | | |
| 16 | • | | | |
| 284 | | | | |
| I.S. EN 13242:2 | - | | | |
| | | | | |
| Aggregates for hydraulically bo civil engineering and | | | | |
| 0/125 (S.R. 21 ANN | | | | |
| Castletown Quarry, Ra | - | | | |
| CT/78 | | | | |
| | | | | |
| Particle size | Designation | 0/125 | | |
| | | -, - | | |
| Aggregate Type / Description | Li | Limestone | | |
| Particle shape | Category | NPD | | |
| Particle density | Declared Value | 2.7 Mg/M ³ | | |
| Cleanliness | | | | |
| Fines content | Category | f ₉ | | |
| Fines quality | Category | NPD | | |
| Percentage of crushed particles | Category | C 100/0 | | |
| Resistance to fragmentation/crushing | Category | LA 30 | | |
| Volume stability | Category | NPD | | |
| Water absorption/suction | Category | WA ₂₄ 2 | | |
| Composition/content | | | | |
| Classification of coarse recycled aggregates | Category | NPD | | |
| Water soluble sulfates of recycled aggregates | Category | NPD | | |
| Acid soluble sulfate | Category | AS 0.2 | | |
| Total sulphur | Category | S 1 | | |
| Consitituents which alter the rate of setting | | | | |
| and hardening of hydraulically bound mixtures | Category | NPD | | |
| Resistance to wear | Category | NPD | | |
| Dangerous substances | | | | |
| Release of heavy metals by leaching | Declared Value | NPD | | |
| | Dealers d Malers | NDD | | |

Release of other dangerous substances

Durability against freeze/thaw

NPD

MS 18

Declared Value

Category