

## **Declaration of Performance**

DOP/CT/78773

#### 4/40 (S.R. 21 ANNEX E - T2 PERM)

Castletown Quarry, Rathmoylon, Co Meath

1. Unique Identification code of the product - type:

Code 78773 - 4/40 (S.R. 21 ANNEX E - T2 PERM)

2. Intened use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction. Including unbound granular fill (Hardcore) for use under concrete floors and footpaths.

3. Manfacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

**6a.** Harmonised Standard: I.S. EN 13242:2002+A1:2007 / S.R. 21:2014+A1:2016 Notified Body: CTI-CEM (2845)

7. Declared performance/s:

Characteristic	Declared Performance		Harmonised Technical Specification	
Particle size	Designation	4/40	EN 933-1	
Particle shape	Category	NPD	EN 933-3	
Particle density	Declared Value	2.7 Mg/m <sup>3</sup>	EN 1097-6	
Aggregate Type / Description	Limestone		EN 932-3	
Fines content	Category	NPD	EN 933-1	
Percentage of crushed particles	Category	C <sub>100/0</sub>	EN 933-5	
Resistance to fragmentation/crushing	Category	LA 30	EN 1097-2	
Water absorption/suction	Declared Value	WA <sub>24</sub> 0.6	EN 1097-6	
Acid soluble sulfate	Declared Value	AS <sub>0.1</sub>	EN 1744-1	
Total sulphur	Declared Value	S <sub>0.1</sub>	EN 1744-1	
Durability against freeze/thaw	Category	MS <sub>18</sub>	EN 1367-2	
Resistance to wear	Category	NPD	EN 1097-1	
Fines quality	Category	NPD	EN 933-9	
Volume stability	Category	NPD	EN 1744-1	
Classification of coarse recycled aggregates	Category	NPD	EN 933-11	
Water soluble sulfates of recycled aggregates	Category	NPD	EN 1744-1	
Consitituents which alter the rate of setting and hardening of hydraulically bound mixtures	Category	NPD	EN 1744-1	
Release of heavy metals by leaching	Declared Value	NPD	EN 13242	
Release of other dangerous substances	Declared Value	NPD	EN 13242	

**8.** N/A

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stephen Greene at Piercetown, Dunboyne, Co Meath on 20th February 2025

Stephen Greene





0

Kilsaran Concrete Piercetown, Dunboyne Co. Meath 16 2845

#### I.S. EN 13242:2002+A1:2007

# Aggregates for hydraulically bound and unbound material for civil engineering and road construction

### 4/40 (S.R. 21 ANNEX E - T2 PERM)

Castletown Quarry, Rathmoylon, Co Meath CT/78773

Particle size	Designation	4/40
Aggregate Type / Description	Li	mestone
Particle shape	Category	NPD
Particle density	Declared Value	2.7 Mg/M <sup>3</sup>
Cleanliness		
Fines content	Category	NPD
Fines quality	Category	NPD
Percentage of crushed particles	Category	C <sub>100/0</sub>
Resistance to fragmentation/crushing	Category	LA <sub>30</sub>
Volume stability	Category	NPD
Water absorption/suction	Category	WA <sub>24</sub> 2
Composition/content		
Classification of coarse recycled aggregates	Category	NPD
Water soluble sulfates of recycled aggregates	Category	NPD
Acid soluble sulfate	Category	AS <sub>0.2</sub>
Total sulphur	Category	S <sub>1</sub>
Consitituents which alter the rate of setting		
and hardening of hydraulically bound mixtures	Category	NPD
Resistance to wear	Category	NPD
Dangerous substances		
Release of heavy metals by leaching	Declared Value	NPD
Release of other dangerous substances	Declared Value	NPD
Durability against freeze/thaw	Category	MS <sub>18</sub>