

Declaration of Performance

DOP/AN/68969

0/100 (100mm Down)

Annagor Quarry, Duleek, Co Meath

1. Unique Identification code of the product - type:

Code: 68969 - 0/100 Ga75 (100mm Down)

2. Intended use/es: Hydraulically bound and unbound materials for use in civil engineering and road construction

3. Manfacturer: Kilsaran Concrete, Piercetown, Dunboyne Co. Meath

4. Authorised Representative: N/A

5. System of AVCP: System 2+

6a. Harmonised Standard: I.S. EN 13242:2002+A1:2007

Notified Body: NSAI (0050-CPR-0209)

7. Declared Performance

| Characteristic | Declared Performance | | Harmonised Technical Specification |
|---------------------------------------------------------------------------------------------------|----------------------|----------------------|------------------------------------|
| Particle size | Designation | 0/100 Ga75 | EN 933-1 |
| Particle shape | Category | NPD | EN 933-3 |
| Particle density | Declared Value | 2.7 Mg/m^3 | EN 1097-6 |
| Aggregate Type | Category | Limestone | EN 932-3 |
| Fines content | Category | NPD | EN 933-1 |
| Percentage of crushed particles | Category | C 100/0 | EN 933-5 |
| Resistance to fragmentation/crushing | Category | LA 30 | EN 1097-2 |
| Water absorption/suction | Declared Value | WA ₂₄ 0.5 | EN 1097-6 |
| Acid soluble sulfate | Declared Value | AS NR | EN 1744-1 |
| Total sulphur | Declared Value | S _{NR} | EN 1744-1 |
| Durability against freeze/thaw | Category | MS 18 | EN 1367-2 |
| Resistance to wear | Category | NPD | EN 1097-1 |
| Fines quality | Category | NPD | EN 933-9 |
| Volume stability | Category | NPD | EN 1744-1 |
| Classification of coarse recycled aggregates | Category | NPD | EN 933-11 |
| Water soluble sulfates of recycled aggregates | Category | NPD | EN 1744-1 |
| Consitituents which alter the rate of setting and hardening of hydraulically bound mixtures | Category | NPD | EN 1744-1 |
| Release of heavy metals by leaching | Declared Value | NPD | EN 13242 |
| Release of other dangerous substances | Declared Value | NPD | EN 13242 |

8. N/A

https://www.kilsaran.ie/technical-library/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Clane Me Chay

Clare McElroy at Piercetown, Dunboyne, Co Meath on 08/02/2022



CE

0050

Kilsaran Concrete

Piercetown, Dunboyne Co. Meath

17

0050-CPR-0209

I.S. EN 13242:2002+A1:2007 Aggregates for hydraulically bound and unbound material for civil engineering and road construction

0/100 (100mm Down)

Annagor Quarry, Duleek, Co Meath

AN/68969

| Particle size | Designation | 0/100 Ga75 |
|-----------------------------------------------|----------------|-----------------------|
| Aggregate Type | Limestone | |
| Particle shape | Category | NPD |
| Particle density | Declared Value | 2.7 Mg/M ³ |
| Cleanliness | | |
| Fines content | Category | NPD |
| Fines quality | Category | NPD |
| Percentage of crushed particles | Category | C 100/0 |
| Resistance to fragmentation/crushing | Category | LA 30 |
| Volume stability | Category | NPD |
| Water absorption/suction | Category | WA ₂₄ 2 |
| Composition/content | | |
| Classification of coarse recycled aggregates | Category | NPD |
| Water soluble sulfates of recycled aggregates | Category | NPD |
| Acid soluble sulfate | Category | AS NR |
| Total sulphur | Category | S _{NR} |
| Consitituents which alter the rate of setting | | |
| and hardening of hydraulically bound mixtures | Category | NPD |
| Resistance to wear | Category | NPD |
| Dangerous substances | | |
| Release of heavy metals by leaching | Declared Value | NPD |
| Release of other dangerous substances | Declared Value | NPD |
| Durability against freeze/thaw | Category | MS 18 |